



45370 SQUARE REGRESSED GIMBAL



The Midway collection is a family of integrated led recessed lights available in sizes ranging from 2"-6". With their durable die cast aluminum bodies and built on CCT color selecting switch Midway family fixtures are aesthetically appealing, functional and extremely versatile. Their IC rated shallow bodies allow them to be used in most residential and commercial installations with or without insulation in the ceiling. Midway fixtures are available in white or black finish and come standard with a reliable phase dimming power supply.

TYPE:		
DATE:		
NOTES:		



2700K . 3000K . 3500K . 4000K . 5000K

SPECIFICATIONS

LIGHT HOUSING

- IC Airtight Cast aluminum body.
- Remodel application. C/W spring loaded clips.
- Mates to driver box with quick connector.
- Max Ceiling thickness 5/8".
- Approved for damp location.

DIMENSIONS

- Cut hole: ø3 3/4".
- Fixture: ø4 3/8" x 3 1/4"H.

ELECTRICAL

- 120 V Input class 2 constant current dimmable driver enclosed in junction box.
- TRIAC and ELV dimming.
- Min operating temperature (-4°F~104°F)(-20°C~-40°C).

LIGHT MODULE

- 1 x 12W Integrated LED COB.
- · Lumen maintenance 70% 50,000 hrs.
- CRI: 90+
- · Beam angle: 38 degree.
- |30K |35K 40K |50K Kelvin (CCT): 27K
- Delivered Lumen: 705 lm |747 lm |812 lm |848 lm |847lm

CERTIFICATIONS













ORDERING GUIDE

MODEL	FINISH
45370-021	Black
45370-014	White

BEAM WATTS LUMENS KELVIN DIMMABLE CRI **ADJUSTABLE** ANGLE TRIAC/ELV 38° 15° ø3 3/4' 12W Up to 848 **CCT Selectable** 90+









PRODUCT DIMENSIONS

12 5/8" 3 3/8" 3 3/16" 3 3/8" QUICK CONNECT 3/8 1 1/8" 4 3/8'

ACCESSORIES



45611-018 2 pin Connector



45372-018 **NEW CONSTRUCTION PLATE** Mounting kit includes bars 14" x 7 3/4" ø3 3/4"



45517-013 **NEW CONSTRUCTION SMASH PLATE** 13 1/4" x 6 1/2" ø3 3/4



NO IC BOX **REQUIRED**