


# Product Specifications Report



<b>Job Name:</b>		<b>Job Type:</b>	
<b>Comments:</b>		<b>Quantity:</b>	
<b>Product Number: 9380-12</b>		<b>Dimensions:</b>	
 <p><b>9380-12 - Black Wiring Connector</b>                  Black Polycarbonate Wiring Connector</p> <p>Polycarbonate tap off connector. Use to tap off of low voltage Ambiance® cable and create a parallel run for shelving, ect. Corrosion resistant contacts pierce the specially designed Ambiance® cable for electrical connection. UL and C-UL listed 12v and 24v. Wet location 12v only. Maximum wattage after connector on 105°C Ambiance® tap cable: 200 at 12v; 375w at 24v.</p> <p><b>UPC #:</b> 785652938023      <b>Product Type:</b> Ambiance LX</p> <p><b>Finish:</b> Black (12)</p>		<b>Length:</b> 1 1/2" <b>Switch Type:</b> N/A <b>Width:</b> 1 1/2" <b>Mounting Proc.:</b> N/A <b>Height:</b> 7/16"	
		<b>Material List:</b>	
		1 Connector - Polycarbonate - Black	
		<b>Safety Listing:</b>	
		cUL Listed for Wet Locations UL Listed for Wet Locations	
<b>Instruction Sheets</b>			
		English (HC-126)	

Shipping Information									
Package Type	Quantity	UPC	Length	Width	Height	Cube	Weight	UPS Ship	Label
Individual	1	785652938023	1.5	1.5	0.5	0.001	0.04	Yes	
Master Pack	10	10785652938020	8.75	6.5	2.25	0.074	0.4	Yes	
NJ Pallet	35000		48	40	60	66.667	1505	No	
NV Pallet	35000		48	40	60	66.667	1505	No	