



## PRODUCT DETAILS:

- $\bullet\,$  For LED lamping, a 6.5w GU10 LED bulb is recommended: GU10LED-3K
- Suitable for use in wet (outdoor direct rain) locations as defined by NEC and CEC. Meets
  United States UL Underwriters Laboratories & CSA Canadian Standards Association Product
  Safety Standards
- Vapor's stunning crackled glass casts spectacular light patterns, adding dramatic visual interest at night
- 2-year finish warranty
- ADA compliant
- Bold lines and a clean, minimalist style complement contemporary architecture
- Mounting hardware is hidden on the back plate to ensure a clean silhouette

## **VAPOR**

## 2855TT

## LARGE WALL MOUNT LANTERN

Vapor's streamlined profile allows the spectacular crackled glass to star in this captivating design. The low profile back plate and stamped metal construction project a sleek, contemporary style statement.

| DETAILS   |                                 |
|-----------|---------------------------------|
| FINISH:   | Titanium                        |
| MATERIAL: | Aluminum                        |
| GLASS:    | Crackle                         |
| DIMMABLE: | YES - CL TYPE DIMMER<br>(SSL7A) |

| DIMENSIONS     |           |
|----------------|-----------|
| WIDTH:         | 4.8"      |
| HEIGHT:        | 28"       |
| WEIGHT:        | 5lb       |
| BACK PLATE:    | 4.75" Sq. |
| EXTENSION:     | 3.8"      |
| TOP TO OUTLET: | 14.2500"  |

| LIGHT SOURCE  |                                 |
|---------------|---------------------------------|
| LIGHT SOURCE: | Socketed                        |
| LED NAME:     | GU10LED-6.5                     |
| WATTAGE:      | 1-7w GU10 LED, 35w<br>Equiv.    |
| VOLTAGE:      | 120v                            |
| COLOR TEMP:   | 2700                            |
| CRI:          | 80                              |
| DIMMABLE:     | YES - CL TYPE DIMMER<br>(SSL7A) |

| SHIPPING       |     |
|----------------|-----|
| CARTON LENGTH: | 10  |
| CARTON WIDTH:  | 7.5 |
| CARTON HEIGHT: | 31  |
| CARTON WEIGHT: | 6.5 |



PHONE: (440) 653-5500

Toll Free: 1 (800) 446-5539