

SIDE ELEVATION SUPPORT MOUNTING DETAIL

FRONT ELEVATION SUPPORT MOUNTING DETAIL

8

SIDE ELEVATION

## FRONT ELEVATION

MODEL	OUTPUT	SUPPLY	SUPPLY	SUPPLY AMP	SUPPLY VOLTAGE/	DIMENSIONS	WEIGHT	SUPPORT MOUNT
	WATTAGE	VOLTAGE	PHASE	DRAW	CONNECTION			AXB
EW15L12	1500 W	120 V	1	12.5A	1Ф2W,120 VAC	57 X 8 X 3"	16.5 LBS (7.5 KG)	47 X 3.8"
						(145 X 20 X 8 CM)		(120 X 9.6CM)
EW32L24	3200 W	240 V	1	13.3A	1Ф2W, 240VAC	89 X 8 X 3"	25.1 LBS (11.4 KG)	70 X 3.8"
					• , • •	(226 X 20 X 8 CM)		(180 X 9.6CM)

NOTES:

- 1. INSTALLATION TO BE COMPLETED IN ACCORDANCE WITH MANUFACTURER'S SPECIFICATIONS.
- 2. DO NOT SCALE DRAWING.
- 3. THIS DRAWING IS INTENDED FOR USE BY ARCHITECTS, ENGINEERS, CONTRACTORS, CONSULTANTS AND DESIGN PROFESSIONALS FOR PLANNING PURPOSES ONLY.
- 4. ALL INFORMATION CONTAINED HEREIN WAS CURRENT AT THE TIME OF DEVELOPMENT BUT MUST BE REVIEWED AND APPROVED BY THE PRODUCT MANUFACTURER TO BE CONSIDERED ACCURATE.
- 5. CONTRACTOR'S NOTE: FOR PRODUCT AND COMPANY INFORMATION VISIT www.CADdetails.com/info AND ENTER REFERENCE NUMBER 5029-022.

IRE EWAVE®

LONG WAVE INFRARED HEATER - SRP EWAVE L:SINGLE PHASE 120/240V (EW15L12/EW32L24)

5029-022

REVISION DATE 13/06/2024