

PANDORA
WS25125-UNV

WALL

PROJECT



WS25125-BN-UNV
Brushed Nickel



WS25125-BG-UNV
Brushed Gold



WS25125-WH-UNV
White



WS25125-BK-UNV
Black


SPECIFICATION DETAILS

Fixture Dimensions	W4-5/8" x H28" x E3-7/8"
Light Source	LED with DC Driver
Wattage	20W
Total Lumens	1440lm
Delivered Lumens	BG- 1102lm BK-965lm BN- 1101lm WH- 1127lm
Voltage	120-277V
Color Temperature	3000K
CRI (Ra)	90CRI
Optional Color Temps	2700K - 5000K Available, Minimum Order Quantities Apply
LED Rated Life	50,000 hours
Dimming	100% - 10%, TRIAC or ELV Dimmer (Not Included)
Diffuser Details	White Acrylic Diffuser
ADA Compliant	Yes
Location	Dry
Illumination Direction	Fontlight Illumination
Mounting Style	All Orientation; Wall;
CEC Title 24 JA8	Yes, JA8-2022
Canopy Dimensions	W4-5/8" x H5-3/8" x E2"
Paint Finish	BK02; BN02; WH02; BG01
Height to Center	25-3/8"
Material	Aluminum + Acrylic

* For custom options, consult factory for details.
* For warranty information, please visit www.kuzcolighting.com/warranty

DESCRIPTION

Square profile linear aluminum with rectangular wall mount. Inset opal polymeric diffuser. Finely textured plate or powder-coated finish. Wall emitting light with rotational adjustment.



KUZCO

CANADA: 19054 28TH AVENUE - SURREY, BC V3Z 6M3
USA: 3035 E. LONE MOUNTAIN ROAD - LAS VEGAS, NV 89081

WWW.KUZCOLIGHTING.COM

© 2024 KUZCO LIGHTING. ALL RIGHTS RESERVED.

COMMENT

