



ASSEMBLING & INSTALLATION INSTRUCTIONS

The drawing shown may not exactly match the product enclosed.

However, the installation instructions do apply to this product.

51052 51053 51054 51055 52133 52134 52135 52136 52141 52142
51042 51043 51044 51045 51082 51083 51084 51085 52140 52139
52151 52152 52153 52154 52158 51362 58061 58062 58063 58064
58068 46267 46268 46269 46741 46743 46744 58854 58855 58856

- ◆ **WARNING! SHUT POWER OFF AT FUSE OR CIRCUIT BREAKER.**
- ◆ **ATTENTION! COUPER LE COURANT AU FUSIBLE OU UN DISJONCTEUR.**

ASSEMBLING THE FIXTURE (Fig.1)

1. Shut off the power at the circuit breaker box. Remove old fixture and all hardware from Junction Box.
2. Carefully unpack your new fixture and lay out all the parts on a clear area. Take care not to lose any small parts necessary for installation.
3. Thread the two mounting screws about 1/4" into the pre-drilled holes in the mounting plate spaced the same distance apart as the holes in the canopy (I).

4. Attach the mounting plate to the Junction Box with the two Junction Box Screws as shown. The side of the mounting plate marked "GND" must face out. **The junction box is not included.**

5. Attach the tube(B) to the top center pipe nipple of the shade(C), turn it until tighten. Attach the canopy(I) to the tube(B), by turning it clockwise until tight.

NOTE: THE SHADE(C) OF THE PRODUCT MAY VARY.

6. Thread the pipe nipple (D) into the bottom center coupling of the lamp holder and lock it securely with the hex nut.

7. Install the light bulbs(not included) in accordance with the fixture specifications.

NOTE: DO NOT EXCEED THE SPECIFIED WATTAGE!

8. Raise the steel shim (E), diffuser(F) and plastic shim (G) to the bottom of the shade (C), aligning the hole with pipe nipple and lock it securely with the finial (H).

9. While holding the shade assembly towards the ceiling, connect the electrical wires as Shown in **Fig.2**, making sure that all wire nuts are secured. You may have to wrap the connections with electrical tape. If your outlet has a ground wire (green or bare copper), connect the fixture ground wire to it. Otherwise connect fixture's ground wire directly to the mounting plate with the green screw provided. After wires are connected, tuck them carefully inside the Junction Box.

10. Raise the shade assembly onto the junction box, aligning screws on mounting plate with mounting holes in canopy (I) and lock it securely with the ball nuts(A).

Your installation is now complete. Return power to the junction box and test the fixture.

FIG.1





FIG.2



Thank you for purchasing a **LIVEX** product.
Need assistance with parts or assembly? Please call customer service at: **800-761-8056**
Or visit us on-line at: WWW.LIVEXLIGHTING.COM