

Dlane

Performance and Precision

Designed to transform any space with its powerful airflow. With a sweeping 90° forward and reverse oscillation, it ensures every corner of the room is touched by its refreshing breeze. Perfectly suited for small, hard-toreach spaces or positioned strategically in front of HVAC ducts, the Diane enhances the efficiency of your heating, ventilation, and air conditioning, making every breath you take feel effortless and pure. Crafted from durable cast aluminum and heavy stamped steel, the Diane is built to last, backed by a limited lifetime warranty that promises years of reliable, silent comfort.





DI-BN-MTL Brushed Nickel Finish with Metal Blades



DI-BK-WDBW Matte Black Finish. with Barn Wood Tone Blades



DI-BN-WDBK Brushed Nickel Finish. with Matte Black Blades

PRODUCT FEATURES







Optional 60° Slant Mount

FAN FEATURES

Fan Weight 12 lbs **Downrod Lengths**

inches: 5, 10, 18, 24, 36, 48, 60, 72

122, 153, 183

Downrod Diameter 1 inch

+ downrod length

Overall Drop Wood 12in / 30cm

A Damp Location

Unipack Shipping

30° Slant Ceiling Canopy Safety Cage Compatible

MOTOR FEATURES

Motor Type AC Ambiance Soothing White Noise RPM (Low/High) **Safety Certification ETL/CETL** Warranty Limited Lifetime

SKU BUILDER

DI-XX-XXXX (Model+Finish+Blade)

FAN FINISHES

Fan Finishes Metal Blades



Matte Black



Blade Finishes

Barn Wood Tone



WD Mahogany Tone

CRPolished Chrome



WDBK Matte Black

Textured Bronze

DOE MOTOR EFFICIENCY DATA

Guard Options

Wood - No Cage Option

Metal - Safety Cage or Decorative Cage

CFM/Watt (High) **Wood** - 865 / 1325 **Wood** - 44

CFM (Low/High) Wood - 1441 / 2152

Metal - 900/1325

Blade Pitch Wood - 19° **Metal** - 1068 / 1345 Metal - 31°

Metal - 31

Watts (High) Wood - 51.37 **Metal** - 46.14

FAN DIAMETER

Solid Wood 16in / 41cm Metal with Guard 13in / 33cm

STANDARD EQUIPMENT

Downrod 10in / 25cm **Slant Ceiling Canopy** 29°



Handheld Remote

- 3 Speed

Oscillation On/Off

*For more information see accessory page. 132

Voltage 110 or 220

centimeters: 13, 25, 46, 61, 92, Field cuttable, Non-threaded

Overall Drop Metal 14in / 36cm

+ downrod length

TECHNICAL SPECIFICATIONS

