

CALIBRO | OUTDOOR SCONCE

86431 | 86433 | 86435

- Aluminum Construction
- 120-277V LED driver
- Dimmable
- CRI 90+
- Black Finish
- 8Uf_G_mcdhjb Uj UjUVY

Job Name : _____

Job Type : _____

Quantity : _____

Comments : _____



PRODUCT DESCRIPTION

Reducing the scale of the classic cylinder sconce is intended for use in applications needed to meet ADA requirements. The sconce profiles extend vertically casting ample light both upwards and downwards. Concealed within the frame, there is a range voltage 120-277V LED driver making this a great option for light commercial as well as residential applications.

FINISHES OPTION

Black

MATERIAL

Aluminum, Glass


RATINGS *Dark Sky Optional

cETLus
Wet Location
ADA



ADDITIONAL

INSTALL UP/DOWN: Up
RATED LIFE 25000 Hours
OPERATING TEMPERATURE:
-20°C (-4°F), 40°C (104°F)



MEASUREMENTS

MODEL	DIMENSION	BACK PLATE	HANGING WEIGHT
86431	2.5"W x 7.5"H x 3.25"Ext	4.5"W X 4.5"H X 3.75"HCO	2 lb
86433	2.5"W x 14.5"H x 3.25"Ext	4.5"W X 4.5"H X 7.25"HCO	2.74 lb
86435	2.5"W x 19.75"H x 3.25"Ext	4.5"W X 4.5"H X 9.75"HCO	3.3 lb

LAMPING

MODEL	BULB TYPE	LUMENS
86431	2 x 7W (14W Total) LED DC Integrated 3000K	1,400 1190 120V-277
86433	2 x 7W (14W Total) LED DC Integrated 3000K	1,400 1190 120V-277
86435	2 x 7W (14W Total) LED DC Integrated 3000K	1,400 1190 120V-277

Always consult a qualified electrician before installing any lighting product.



WESTERN DISTRIBUTION CENTER (HEADQUARTER)
253 NORTH VINELAND AVE | CITY OF INDUSTRY, CA 91746
EASTERN DISTRIBUTION CENTER
101 GARDNER PARK | PEACHTREE CITY, GA 30269
P. 626.956.4200 | F. 626.956.4225 | maximlighting.com