
MODERN FORMS SMART FANS





PRODUCT DESCRIPTION

Finished in gloss black or glistening automotive silver, Stargazer has an elevated look that's right on par with the smart technology inside. Powered by our exclusive Modern Forms app, the smart fan offers unprecedented control over scheduling, energy use and home integration- it's compatible with Amazon Alexa, Google Assistant and other devices you already own. A powerful, highly efficient LED luminaire projects down from the center for final a luxe touch.

SPECIFICATIONS

Construction: Aluminum

Blade: 14° Pitch, 52" sweep, ABS

Downrod: 1" O.D. x 4.5"H included

Mounting Slope: Up to 30°

Lead Wire: 80"

Hanging Weight: 16 lbs Total Power: 49W

Standards: ETL/cETL Wet Location listed

FEATURES

- 6 fan speeds through both Summer and Winter Modes
- Silent DC motor
- Optional LED light kit included
- Includes RF wall control
- Additional RF wall control for 3, 4-way control sold separately
- Compatible with Modern Forms app

LIGHT KIT PERFORMANCE

Light Source: LED Light Wattage: 13W Dimming: Integrated Color Temperature: 3000K Rated Life: 50,000 Hours

Standards: Title 24 JA8-2016 compliant

ESTIMATED AIR PERFORMANCE

Airflow: 6032 cubic ft per minute on high

Power: 36 watts on high

Airflow Efficiency: 170 cubic ft per minute per watt

Revolutions Per Minute: 148 RPMs on high/96 RPMs on average

WIRELESS PERFORMANCE

RF Pairing Distance: Up to 30 ft from fan

Wi-Fi Range: Up to 150 ft*


ORDER NUMBER

Model	LED Lumens	Delivered Lumens		Housing		Blade	
FR-W1804-52L			GB	Gloss Black	WG	Weathered Gray	
	1110	347	AS	Automotive Silver		Automotive Silver	
			LN	Liquid Nickel		Liquid Nickel	

Example: FR-W1804-52L-GB/LN

*Results may vary based on application and surroundings.







OPTIONAL ACCESSORIES

RF Wall Control	F-WC	WT White	Control fan speed, light brightness and switch between Summer and Winter Modes from up to 30 ft away. One RF Wall control comes standard with each Modern Forms Smart fan.
Wi-Fi Touch Panel Wall Control	F-TS	BK Black WT White	Sold separately. Android tablet comes pre-loaded with Modern Forms app, Wi-Fi range up to 150 ft from router. Results may vary based on application/surroundings.
Downrod Couplers	XF-12 12in XF-18 18in XF-24 24in XF-36 36in XF-48 48in XF-60 60in XF-72 72in	AS Automotive Silver BZ Bronze CFI Carbon Fiber** DW Dark Walnut GB Gloss Black GH Graphite GW Gloss White MB Matte Black	All our downrods are 1" O.D. and are threaded on the motor end to create an extra layer of security and allow for adjustments in the field. Connects two downrods together.
Sloped Ceiling Kit XF-SCK		MW Matte White OB Oil Rubbed Bronze SS Stainless Steel TT Titanium Silver	Designed to accommodate buildings with steeper sloped ceilings up to 45° or 12/12 pitch.

Examples: RF Wall Control - **F-WC-WT**, Wi-Fi Touch Panel - **F-TS-WT**, Downrod - **XF-12-BZ**, Downrod Coupler - **XF-I-BZ**, Sloped Ceiling Kit - **XF-SCK-DW NOTE:** Recommended maximum downrod length of 72" with 80" lead wire.

SUGGESTED DOWNROD HEIGHT USAGE

Ceiling Height	15′	14′	13′	12′	11′	10′	9'
Downrod	72"	60"	48"	36"	24"	18"	12"

SLOPED CEILING DEGREE CONVERSION CHART

Degree	4-8°	9-13°	14-17°	18-21°	22-25°	26-29°	30-32°	33-35°	36-38°	39-41°	42-44°	45°
Ceiling Slope	1/12	2/12	3/12	4/12	5/12	6/12	7/12	8/12	9/12	10/12	11/12	12/12
Pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch	pitch

Supplied mounting brackets allow mounting on ceiling slopes up to 30° (7/12 pitch). Optional slope kit allows mounting on ceilings up to 45° (12/12 pitch). The receiver will mount inside canopy up to 45°.

^{**}Carbon Fiber downrods available in 12", 18", 24" and 36"