



PRODUCT DESCRIPTION

A luminous architectural profile and superior construction make this sconce appropriate for transitional and contemporary interiors or exteriors. Mitered silk-screened glass encases a maximum number of LEDs engineered for optimal illumination. Three sizes allow for cohesive specifications across residential and commercial interior and exterior applications.

FEATURES

- ETL & cETL listed for wet locations, IP65
- CEC Title 24 Compliant
- Low profile design
- Replaceable LED module
- 200° beam angle
- 277V option available for 1408, 1414 and 1220 special order
- 80,000 hour potential life
- Color Temp: 3000K
- CRI: 90

SPECIFICATIONS

Construction: Aluminum with white mitered glass.

Power: Transformer located in outlet box

Light Source: High output LED

Dimming: Dims to 10% with an electronic low voltage (ELV) dimmer

Mounting: Mounts directly to junction box

Finish: Brushed Aluminum (AL), Black (BK). Bronze (BZ), Graphite (GH)

Standards: ETL & cETL listed. ADA compliant.

Installation: Requires Transformer to be recessed within the junction box.

Model	Height	Watt	Voltage	LED Lumens	Delivered Lumens	Finish
WS-W1408 WS-W1414 WS-W1420	8" 14" 20"	11.5W 19.5W 29W	120V	525 910 1575	340 670 1050	AL Brushed Aluminum BK Black BZ Bronze GH Graphite

Example: WS-W1420-AL

For 277V special order, add an "F" before the finish: WS-W1420F-AL

Model	Length	Watt	Voltage	LED Lumens	Delivered Lumens	Finis	h	
WS-W1412	12"	29W	120V	1200	690	BK BZ	Brushed Aluminum Black Bronze Graphite	

Example: WS-W1412-AL

modernforms.com Phone (800) 526.2588 Fax (800) 526.2585 Headquarters/Eastern Distribution Center 44 Harbor Park Drive Port Washington, NY 11050 **Central Distribution Center** 1600 Distribution Ct Lithia Springs, GA 30122 Western Distribution Center 1750 Archibald Avenue Ontario, CA 91760

WAC Lighting retains the right to modify the design of our products at any time as part of the company's continuous improvement program. AUG 2015

REPLACEMENT GLASS

Model	Fixture	Description		
RPL-GLA-1408-01	WS-W1408			
RPL-GLA-1414-01	WS-W1414	Outside Glass		
RPL-GLA-1420-01	WS-W1420			
RPL-GLA-1408-02	WS-W1408			
RPL-GLA-1414-02	WS-W1414	Inside Glass		
RPL-GLA-1420-02	WS-W1420			