



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____



65-1661 - 20/30/40 Wattage Selectable LED 2ft x 2ft Backlit
Panel: 35K/4K/5K CCT Selectable; 120-277 Range Voltage

- Wattage Selectable
- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	20W/30W/40W
Volts:	120V-277V
Lumens:	2500L/3750L/5000L
Lamp Base :	Integrated - Integrated
CRI:	80+
CCT (Kelvins):	35K/40K/50K - Neutral White to Natural Light
Beam Spread :	120
Hours Rated:	50000
Dimmable:	Yes-Dimmable - 0-10V Dimming
Incandescent Equivalent :	200W
Operating Temperature :	-17C (+1.4F) to +45C (+113F)
Lamp Included :	Integrated
Replaceable Light Source :	No
Connection:	Hardwire
Surge Protection :	Built-in surge protection - 2KV
THD:	<20%
Power Factor :	0.9
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PHYSICAL

Finish:	White
Lens Finish:	White
Lens Material:	Polystyrene (PS)
Dimensions:	L:23.74" W:23.74" H:1.38"
Weight (Lbs.):	4.12
Material:	Die-Cast Aluminum
Panel Size:	2x2

COMPLIANCE

Safety Listing:	cULus - Certified
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	Yes
DLC Classification:	Premium
DLC ID:	S-2S0B17
CA Prop 65:	Lead
BAA Compliant:	No
FCC Compliant:	Yes
IP Rating:	IP20
RoHS Compliant:	Yes
Restrictions:	No Restrictions

PACKAGING

Each UPC:	045923411779
Each Quantity:	1
Each Dimensions:	24.33 x 2.91 x 24.61




65-1661 - 20/30/40 Wattage Selectable LED 2ft x 2ft Backlit Panel; 35K/4K/5K CCT Selectable; 120-277 Range Voltage

ACCESSORIES

	65-1610	4 Foot Backlit Panel Suspension Kit
---	----------------	-------------------------------------

	65-1612	2x2 Surface Mount Kit; White Finish
---	----------------	-------------------------------------

	65-1615	2x2 Flange Kit; White Finish
---	----------------	------------------------------
