



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_



**65-1662** - 30/40/50 Wattage Selectable LED 2ft x 4ft Backlit  
Panel; 35K/4K/5K CCT Selectable; 120-277 Range Voltage

- Wattage Selectable
- CCT Selectable



### ELECTRICAL

Technology:	LED
Watts:	30W/40W/50W
Volts:	120V-277V
Lumens:	3750L/4500L/6250L
Lamp Base :	Integrated - Integrated
CRI:	80+
CCT (Kelvins):	35K/40K/50K - Neutral White to Natural Light
Beam Spread :	120
Hours Rated:	50000
Dimmable:	Yes-Dimmable - 0-10V Dimming
Incandescent Equivalent :	250W
Operating Temperature :	-17C (+1.4F) to +45C (+113F)
Lamp Included :	Integrated
Replaceable Light Source :	No
Connection:	Hardwire
Surge Protection :	Built-in surge protection - 2KV
THD:	<20%
Power Factor :	0.9
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

### PHYSICAL

Finish:	White
Lens Finish:	White
Lens Material:	Polystyrene (PS)
Dimensions:	L:47.76" W:23.74" H:1.38"
Weight (Lbs.):	8.03
Material:	Die-Cast Aluminum
Panel Size:	2x4

### COMPLIANCE

Safety Listing:	cULus - Certified
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	Yes
DLC Classification:	Premium
DLC ID:	S-FPBCM2
CA Prop 65:	Lead
BAA Compliant:	No
FCC Compliant:	Yes
IP Rating:	IP20
RoHS Compliant:	Yes
Restrictions:	No Restrictions




### PACKAGING

Each UPC:	045923411786
Each Quantity:	1
Each Dimensions:	48.46 x 2.91 x 24.33



**65-1662** - 30/40/50 Wattage Selectable LED 2ft x 4ft Backlit Panel; 35K/4K/5K CCT Selectable; 120-277 Range Voltage

ACCESSORIES

	<b>65-1610</b>	4 Foot Backlit Panel Suspension Kit
	<b>65-1611</b>	2x4 Surface Mount Kit; White Finish
	<b>65-1616</b>	1x4 Flange Kit; White Finish