





Location:

Fixture Type:

Notes:



• Wattage Selectable

• CCT Selectable











ELECTRICAL

Technology:	LED	
Watts:	20W/30W/40W	
Volts:	120V-277V	
Lumens:	2500L/3750L/5000L	
Lamp Base : Integrated - Integr		
CRI:	80+	
CCT (Kelvins):	35K/40K/50K - Neutral White to	
	Natural Light	
Beam Spread :	120	
Hours Rated:	50000	
Dimmable: Yes-Dimmable - 0-10V Dimm		
Incandescent Equivalent :	200W	
Operating Temperature :	-17C (+1.4F) to +45C (+113F)	
Lamp Included :	Integrated	
Replaceable Light Source :	No	
Connection:	Hardwire	
Surge Protection :	Built-in surge protection - 2KV	
THD:	<20%	
Power Factor :	0.9	
Voltage Type:	AC Only; Range Voltage	
Warranty:	5-Years	

PHYSICAL

Finish:	White
Lens Finish:	White
Lens Material:	Polystyrene (PS)
Dimensions:	L:47.76" W:11.93" H:1.38"
Weight (Lbs.):	4.25
Material:	Die-Cast Aluminum
Panel Size:	1x4

COMPLIANCE

Safety Listing:	cULus - Certified	
Location Rating:	Damp	
Indoor/Outoor:	Indoor	
DLC Approved:	Yes	
DLC Classification:	Premium	
DLC ID:	S-NBWDB3	
CA Prop 65:	Lead	
BAA Compliant:	No	
FCC Compliant:	Yes	
IP Rating:	IP20	
RoHS Compliant:	Yes	
Restrictions:	No Restrictions	

PACKAGING

Each UPC:	045923411793
Each Quantity:	1
Each Dimensions:	48.46 x 2.91 x 12.52



65-1663 - 20/30/40 Wattage Selectable LED 1ft x 4ft Backlit Panel; 35K/4K/5K CCT Selectable; 120-277 Range Voltage

ACCESSORIES

7.0020011		
×	65-1610	4 Foot Backlit Panel Suspension Kit
×	65-1613	1x4 Surface Mount Kit; White Finish
×	65-1614	2x4 Flange Kit; White Finish