



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**65-1667** - 20/30/40 Wattage Selectable LED 1ft x4ft Backlit  
Panel; 35K/4K/5K CCT Selectable; Emergency Battery; 120-277  
Range Voltage

- Wattage Selectable
- CCT Selectable
- Has Emergency Battery



## ELECTRICAL

Technology:	LED
Watts:	20W/30W/40W
Volts:	120V-277V
Lumens:	2500L/3750L/5000L
Lamp Base :	Integrated - Integrated
CRI:	80+
CCT (Kelvins):	35K/40K/50K - Neutral White to Natural Light
Beam Spread :	120
Hours Rated:	50000
Dimmable:	Yes-Dimmable - 0-10V Dimming
Incandescent Equivalent :	200W
Operating Temperature :	-17C (+1.4F) to +45C (+113F)
Lamp Included :	Integrated
Replaceable Light Source :	No
Connection:	Hardwire
Surge Protection :	Built-in surge protection - 2KV
THD:	<20%
Power Factor :	0.9
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

## PACKAGING

Each UPC:	045923411823
Each Quantity:	1
Each Dimensions:	48.70 x 2.91 x 12.87

## PHYSICAL

Finish:	White
Lens Finish:	White
Lens Material:	Polystyrene (PS)
Dimensions:	L:47.76" W:11.93" H:2.59"
Weight (Lbs.):	6.39
Material:	Die-Cast Aluminum
Panel Size:	1x4

## COMPLIANCE

Safety Listing:	cULus - Certified
Location Rating:	Damp
Indoor/Outdoor:	Indoor
DLC Approved:	Yes
DLC Classification:	Premium
DLC ID:	S-6MRg1L
CA Prop 65:	Lead
BAA Compliant:	No
FCC Compliant:	Yes
IP Rating:	IP20
RoHS Compliant:	Yes
Restrictions:	No Restrictions