



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-619R1 - LED Flood Light; 150 Watt; 4000K; Bronze Finish



GENERAL

Company	NUVO
EA Height	5.51
EA Width	15.35
EA Length	19.49
Bulb Included	Integrated
Material	Die-cast Aluminum
Fixture Type	Flood Light
Product Notes	Add on photocell, sku 86-212, is only rated for 120-277 Volt
Status	Active
Style	Utility
Surge Protection	Built-in surge protection - 6KV
Total Harmonic Distortion	15%
Wire Color	White / Black / Green / Gray / Yellow
Wire Quantity	5
CCT Selectable	No
Wattage Selectable	No
Finish Family	Bronze
Amps	1.250-0.432A
Has Camera	No
IOT Enabled	No
Lens Material	Polycarbonate (PC)
SDS Class	LED_Fixture
Indoor Outdoor	Outdoor
Product Technology	LED
Incandescent Equivalent	450W

ELECTRICAL

CCT (Kelvin Temp)	4000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	150
Color Temp	Cool White
CRI	80+
Dimming Type	0-10V Dimming
Operating Frequency	50-60Hz
Operating Temp	-40F to +122F (-40C to +50C)
Lumens	19500L
Volts	120V-347V
Watts	150W

PHYSICAL

Lamp Base	Integrated
Finish	BRONZE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Rectangle

ADDITIONAL INFO

Warranty	5-Years
----------	---------

PACKAGING

UPC	045923659652
Case Cube	0.954
Case Height	5.51
Case Length	19.49
Case Quantity	1
Case UPC	10045923659659
Case Weight	9.93
Case Width	15.35
EA Cube	0.954
EA Height	5.51
EA Length	19.49
EA Quantity	1
EA Weight	19.52
EA Width	15.35
Pack Type	Box
Web Height	2.83
Web Length	13.82
Web Width	9.44

COMPLIANCE

CA Prop 65	Lead
DLC ID	S-WV6SYK
FCC Compliant	Yes
IC Rated	Yes
IP Rating	IP65
Location Rating	Wet
ROHS Compliant	Yes
Safety Listing	cULus - Certified
California Ban	Lawful for sale
DLC Approved	Yes
Title 20	Exempt
T24 Compliant	No