



Project/Job Name:

Location:

Fixture Type:

Notes:

**65-798R2** - 240 Watt UFO LED High Bay; 5000K; 34560 Lumens;  
120-277 Volt; White Finish



## ELECTRICAL

Technology:	LED
Watts:	240W
Volts:	120V-277V
Lumens:	34560L
Lamp Base :	Integrated
Lamp Shape :	Integrated LED
CRI:	80
CCT (Kelvins):	5000K
Temperature:	Natural Light
Beam Spread :	90
Hours Rated:	50000
Dimmable:	Yes-Dimmable
DimmableText:	0-10V Dimming Only
Incandescent Equivalent :	2000W
HID Equivalent :	700W
Operating Temperature :	-40C (-40F) to +50C (+122F)
Lamp Included :	Integrated
Replaceable Light Source :	No
Number of LEDs :	720
Surge Protection :	Built-in surge protection - 6KV
THD:	15%
Power Factor :	0.9
Warranty:	5 Year Limited - Fixtures

## PACKAGING

Each UPC:	045923648281
Each Quantity:	1
Each Dimensions:	14.17 x 14.17 x 4.92
Case UPC:	10045923648288
Case Quantity:	1
Case Dimensions:	14.17 x 14.17 x 7.99

## PHYSICAL

Finish:	White
Lens Material:	Polycarbonate (PC)
Finish Family:	White
Dimensions:	H:8.11" DIA:13.39"
Weight (Lbs.):	6.42
Material:	Die Cast Aluminum
Sensor:	Optional Add-On

## INSTALLATION

Wire Length:	72 in.
--------------	--------

## COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor
DLC Approved:	Yes
DLC Classification:	Premium
DLC ID:	S-RZCPF8
DLC Primary Use:	High-Bay Luminaires for Commercial and Industrial Buildings
UL/ETL Standard:	UL 1598; CSA-C22.2 No. 250.0
CA Prop 65:	Lead
FCC Compliant:	Yes
IP Rating:	IP65
IK Rating:	IK08
NSF Approved:	Yes
RoHS Compliant:	Yes
SDS Class:	LED_Fixture
Restrictions:	No Restrictions

## INFO

Installation Note:	Mounting Height: Up to 35 feet
Includes:	Locking Hanging Hook; 6 Foot Whip

**ACCESSORIES**

	<b>65-170</b>	Whip Connector; 5.5 Foot; IP68 Rated; White; 0-10V Dimming
	<b>65-200</b>	Whip Connector; 5.5 ft.; IP68 Rated; White
	<b>65-759</b>	3/8" to 3/4" Pendant Adapter; White Finish; For use with Gen 2 and CCT & Wattage Selectable UFO LED High Bay Fixtures
	<b>65-764</b>	Yoke Mount Bracket; White Finish; For Use With Gen 2 200W/240W and CCT & Wattage Selectable UFO High Bay Fixtures
	<b>65-779</b>	Add-On Aluminum Reflector; Use with 200W & 240W Gen 2 UFO LED High Bay Fixtures
	<b>65-799</b>	Add-On PC Shade; Use with 200W & 240W Gen 2 UFO LED High Bay Fixtures
	<b>65-800</b>	Add-On Bottom Diffuser for 200W & 240W Gen 2 UFO LED High Bay Fixtures. Note, must be used in conjunction with 65-799 (PC Shade)
	<b>65-810</b>	Protective Wire Guard for 200W & 240W Gen 2 UFO LED High Bay Fixtures
	<b>65-815</b>	40W Add-On EM Battery Backup; For use with Gen 2 200W/240W and 65/771R1 CCT & Wattage Selectable UFO LED High Bay Fixtures; 40 Watt /90 Min Run Time
	<b>86-217</b>	Add-On PIR Sensor; 6 Meter
	<b>86-218</b>	Add-On Microwave Sensor; 12 Meter
	<b>86-219</b>	Programing Remote Control for use with 86-218, 86-217 & 86-220 Sensors
	<b>86-220</b>	Add-On PIR Sensor; 12 Meter



**65-798R2** - 240 Watt UFO LED High Bay; 5000K; 34560 Lumens;  
120-277 Volt; White Finish

#### DIMMER COMPATIBILITY

LeGrand	ADPD4FBL3P2W4
Eaton	DF10P
Leviton	DS710-10Z
Lutron	DVSCSTV
Lutron	DVSTV
Lutron	DVTV PP347H 347V Only
Leviton	IP710-LFZ
Lutron	MS-Z101
Lutron	MS-Z101-V
Lutron	NTSTV-DV
Lutron	RMJS-8T-DV-B PJ2-3BRL-GWH-L01
Eaton	SF10P