



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-801R2 - 100 Watt UFO LED High Bay; 4000K; 14100 Lumens; 277-480 Volt; Black Finish



ELECTRICAL

Technology:	LED
Watts:	100W
Volts:	277V-480V
Lumens:	14100L
Lamp Base :	Integrated
Lamp Shape :	Integrated LED
CRI:	80
CCT (Kelvins):	4000K
Temperature:	Cool White
Beam Spread :	90
Hours Rated:	50000
Dimmable:	Yes-Dimmable
DimmableText:	0-10V Dimming Only
Incandescent Equivalent :	600W
HID Equivalent :	250W
Operating Temperature :	-40C (-40F) to +45C (+113F)
Lamp Included :	Integrated
Replaceable Light Source :	No
Number of LEDs :	320
Surge Protection :	Built-in surge protection - 6KV
THD:	15%
Power Factor :	0.9
Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923648137
Each Quantity:	1
Each Dimensions:	11.81 x 11.81 x 4.92
Case UPC:	10045923648134
Case Quantity:	1
Case Dimensions:	11.81 x 11.81 x 4.92

PHYSICAL

Finish:	Black
Lens Material:	Polycarbonate (PC)
Finish Family:	Black
Dimensions:	H:8.11" DIA:11.02"
Weight (Lbs.):	6.58
Material:	Die Cast Aluminum
Sensor:	Optional Add-On

INSTALLATION

Wire Length:	72 in.
--------------	--------

COMPLIANCE

Safety Listing:	cULus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor
DLC Approved:	Yes
DLC Classification:	Premium
DLC ID:	S-LHQ20Y
DLC Primary Use:	High-Bay Luminaires for Commercial and Industrial Buildings
CA Prop 65:	Lead
FCC Compliant:	Yes
IP Rating:	IP65
IK Rating:	IK08
NSF Approved:	Yes
RoHS Compliant:	Yes
SDS Class:	LED_Fixture
Restrictions:	No Restrictions

INFO

Installation Note:	Mounting Height: Up to 20 feet
Includes:	Locking Hanging Hook; 6 Foot Whip

ACCESSORIES



65-169 Whip Connector; 5,5 Foot; IP68 Rated; Black; 0-10V Dimming



65-199 Whip Connector; 5,5 ft.; IP68 Rated; Black



65-765 Yoke Mount Bracket; Black Finish; For Use With Gen 2 100W/150W & CCT & Wattage Selectable UFO High Bay Fixtures



65-769 3/8" to 3/4" Pendant Adapter; Black Finish; For use with Gen 2 and CCT & Wattage Selectable UFO LED High Bay Fixtures



65-778 Add-On Aluminum Reflector; Use with 100W & 150W Gen 2 UFO LED High Bay Fixtures



65-780 Add-On EM Battery Backup; For use with Gen 2 100W/150W and 65/770R1 CCT & Wattage Selectable UFO LED High Bay Fixtures; 30 Watt /90 Min Run Time



65-789 Add-On PC Shade; Use with 100W & 150W Gen 2 UFO LED High Bay Fixtures



65-790 Add-On Bottom Diffuser for 100W & 150W Gen 2 UFO LED High Bay Fixtures. Note, must be used in conjunction with 65-789 (PC Shade)



65-809 Protective Wire Guard for 100W & 150W Gen 2 UFO LED High Bay Fixtures



86-218 Add-On Microwave Sensor; 12 Meter



86-219 Programming Remote Control for use with 86-218, 86-217 & 86-220 Sensors
