



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-821R1 - 4 Foot; Vapor Proof Linear Fixture; CCT & Wattage Selectable; IP65 and IK08 Rated; 0-10V Dimming; 120V-347V

- Wattage Selectable
- CCT Selectable
- Has Driver



ELECTRICAL

Technology:	LED
Watts:	40W/50W/60W
Volts:	120V-347V
Lumens:	5360L-7991L
Lamp Base :	Integrated
Lamp Shape :	Integrated LED
CRI:	80
CCT (Kelvins):	3000K/4000K/5000K
Temperature:	Warm to Cool White
Beam Spread :	120
Hours Rated:	50000
Dimmable:	Yes-Dimmable
Dimmable Down To %:	100 to 20 percent
DimmableText:	0-10V Dimming
Incandescent Equivalent :	300W-400W
HID Equivalent :	125W-150W
Operating Temperature :	-40C (-40F) to +45C (+113F)
Lamp Included :	Integrated
Replaceable Light Source :	No
Surge Protection :	Built-in surge protection - 2KV
THD:	17.60%
Power Factor :	>0.96
Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923650963
Each Quantity:	1
Each Dimensions:	49.61 x 5.71 x 3.94
Case UPC:	10045923650960
Case Quantity:	6
Case Dimensions:	49.61 x 11.42 x 11.81

PHYSICAL

Finish:	Gray
Lens Material:	Polycarbonate (PC)
Finish Family:	Gray
Dimensions:	L:47.24" W:4.92" H:3.46"
Weight (Lbs.):	5.07
Material:	Plastic

COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor and Outdoor
Energy Star Qualified:	No
DLC Approved:	Yes
DLC Classification:	Standard
DLC ID:	S-8CX59R
DLC Primary Use:	Direct Linear Ambient Luminaires
CA Prop 65:	Lead
Vapor Tight Fixture Rated:	Yes
FCC Compliant:	Yes
IP Rating:	IP65
IK Rating:	IK08
NSF Approved:	Yes
RoHS Compliant:	Yes
SDS Class:	LED_Fixture
Restrictions:	No Restrictions



65-821R1 - 4 Foot; Vapor Proof Linear Fixture; CCT & Wattage Selectable; IP65 and IK08 Rated; 0-10V Dimming; 120V-347V

DIMMER COMPATIBILITY

LeGrand	ADPD4FBL3P2W4
Eaton	DF10P
Leviton	DS710-10Z
Lutron	DVSCSTV
Lutron	DVSTV
Leviton	IP710-LFZ
Lutron	MS-Z101
Lutron	MS-Z101-V
Lutron	NTSTV-DV
Lutron	RMJS-8T-DV-B PJ2-3BRL-GWH-L01
Eaton	SF10P