



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

65-881 - Oval Small Emergency Wall Pack; LED; CCT Selectable; Photocell; Black Finish

- CCT Selectable
- Has Emergency Battery



ELECTRICAL

Technology:	LED
Watts:	15W
Volts:	120V-277V
Lumens:	1740L-1814L
CRI:	80
CCT (Kelvins):	3500K/4000K/5000K
Beam Spread :	100
Hours Rated:	50000
Dimmable:	Yes-Dimmable
DimmableText:	0-10V Dimming
HID Equivalent :	60W
Operating Temperature :	0C (+32F) to +45C (+113F)
Connection:	Hardwire
Surge Protection :	Built-in surge protection - 2.5KV
THD:	15%
Power Factor :	0.9
Voltage Type:	Range Voltage
Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923650505
Each Quantity:	1
Each Dimensions:	6.77 x 4.06 x 10.83
Case UPC:	10045923650502
Case Quantity:	10
Case Dimensions:	7.28 x 16.81 x 11.61

PHYSICAL

Finish:	Black
Lens Finish:	Prismatic
Lens Material:	Polycarbonate (PC)
Finish Family:	Black
Dimensions:	H:10.47" DIA:6.54" E:3.78"
Weight (Lbs.):	3.61
Material:	Die-cast Aluminum
Sensor:	Has Photocell

COMPLIANCE

Safety Listing:	cULus
Location Rating:	Wet
Indoor/Outdoor:	Indoor; Outdoor
DLC Approved:	Yes
DLC Classification:	Premium
DLC ID:	S-FW6VDL
DLC Primary Use:	Outdoor Non-Cutoff and Semi-Cutoff Wall-Mounted Area Luminaires
CA Prop 65:	Lead
BAA Compliant:	No
FCC Compliant:	Yes
IP Rating:	IP65
IK Rating:	IK08
RoHS Compliant:	Yes
SDS Class:	LED_Fixture
B.U.G Rating:	B1-U3-G1
Restrictions:	No Restrictions

INFO

Additional Info:	Battery Mode: 5 Watts, 90 Minute Run Time
------------------	-------------------------------------------