
ASSEMBLY AND INSTALLATION INSTRUCTIONS

WARNING: TO AVOID RISK OF ELECTRICAL SHOCK, BE SURE TO SHUT OFF POWER PRIOR TO INSTALLING OR SERVICING THIS FIXTURE.

NOTE: Before installing, consult local electrical codes for wiring and grounding requirements.



Installation Steps

- 1. Carefully unpack your new fixture and lay out all the parts on clean surface. Take care not to lose any small parts necessary for installation.
- 2. Feed the wiring from the driver through the mounting box, the back plate, and the mounting strap. Be sure to leave the orange connector accessible.
- 3. Make wire connections: Attach ground wire to building ground wire using a wire nut or attach them to the mounting plate with a green ground screw. Refer to driver label for wire identification.
 - <u>FOR DIMMING</u>: If using a dimmer (not included), follow wiring instructions enclosed with dimmer. Double check wiring. Tuck the wire connections neatly into the junction box.
 - <u>FOR NON-DIMMING</u>: If not using a dimming switch, with wire nuts, cap off purple and gray wires individually. Connect neutral wire (white) with neutral wire, hot wire (black) with hot wire. Double check wiring. Tuck the wire connections neatly into the junction box.
- 4. Secure the mounting strap to the j-box using j-box screws. Then secure the back plate and mounting box to the mounting strap with the screws provided. Be sure to keep both parts level.

 Note: If mounting to a horizontal mud ring, do not use the mounting strap. Secure the back plate and
 - <u>Note</u>: If mounting to a horizontal mud ring, do not use the mounting strap. Secure the back plate and mounting box directly to the mud ring.
- 5. Pick up fixture body, connect the orange connectors, and attach the fixture to the mounting box with the fixture screw.

 HALO sconce
- 6. Turn power back on at fuse or circuit box.

3-535-xx



OXYGEN LIGHTING ©

OXYGEN LIGHTING
201 RAILHEAD RD, FORT WORTH, TX 76106
TEL. (877) 607-0202 FAX (877) 607-0203
WWW.OXYGENLIGHTING.COM