

Project:

Fixture Type:

Location:

Contact:

Phase 1.1 LED

Wall Mounted • Damp Location Listed PROGRESS LED

Description:

Phase 1.1 LED Collection 24" LED Linear Bath & Vanity

Specifications:

- White Acrylic Diffuser
- Dimmable to 10% brightness (See Dimming Notes)
- Back plate covers a standard 4" recessed outlet box: 7.0625 in W., 4.75 in ht., 0.375 in depth
- Mounting plate for outlet box included
- 6 in of wire supplied
- · Americans With Disabilities Act (ADA) compliant

Performance:

Number of Modules	1
Input Power	22 W
Input Voltage	120 V
Input Frequency	50/60 Hz
Lumens/LPW (Delivered)	1,675/76 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Max. Operating Temp	30°C
Warranty	5-year Limited Warranty
Labels	cETLus Damp Location Listed
	Meets California Title 24 JA8-2016



P300223-009-30

Dimensions:

Width: 24 in Depth: 4 in Height: 4-3/4 in H/CTR: 2-3/8 in (mounted horizontal)

White Acrylic Diffuser Width: 23-1/8 in Height: 2-5/8 in



24 in



Phase 1.1 LED

Wall Mounted • Damp Location Listed PROGRESS LED

Dimming Notes:

 $\mathsf{P300223}\text{-}009\text{-}30$ is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

utron_Nova T NTELV-300	
utron_Diva DVELV-300P	
utron_Caseta	
eviton_Trimatron 6681	
utron_Ariadni AYCL-153P	
utron_Maestro MAELV-600	
eviton_AWRMG-EAW	

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.

P300223-009-30