

## CCT Selectable Bath

Wall Mounted • Damp Location Listed 

### Description:

One-Light LED CCT Selectable 26" Linear Cloud

### Specifications:

- White PMMA Diffuser
- Dimmable to 10% brightness (See Dimming Notes)
- Backplate covers a standard 4" recessed outlet box: 23.813 in W., 3.688 in ht., 1.438 in depth
- Mounting backplate for outlet box included
- 6 in of wire supplied

### Performance:

Number of Modules	1
Input Power	24 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	2,124/87.8 (LM-79)
CCT	3000, 4000, 5000 K
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
EMI/RFI	Meets FCC Title 47, Part 15 Class B
Warranty	5-year Limited Warranty
Labels	cETLus Damp Location Listed
	Meets California Title 24 JA8-2016

# P300239-060-CS



### Dimensions:

Width: 26-3/8 in  
Height: 6-1/8 in  
Depth: 4-5/8 in

White PMMA Diffuser  
Width: 26-3/8 in  
Height: 4-5/8 in

**Dimming Notes:**

---

P300239-060-CS is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

**Dimming Controls:**

---

IDevices\_IDEV0009

Leviton\_SureSlide 6672

Lutron\_Diva DVELV-300P

Lutron\_Diva DVCL-253P

Lutron\_Caseta Wireless

Lutron\_Ariadni AYCL-153P

Lutron\_SCL-153P

Lutron\_Toggler TGCL-153PH-WH

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.

**P300239-060-CS**