

LED Bath Light

Wall Mounted • Damp Location Listed **PROGRESS LED**

Description:

One-Light Brushed Nickel LED Bath Vanity

Specifications:

- White PMMA Diffuser
- Dimmable to 10% brightness (See Dimming Notes)
- Backplate covers a standard 4" recessed outlet box: 48 in W., 4.5 in ht., 1.313 in depth
- Mounting backplate for outlet box included
- 6 in of wire supplied

Performance:

Number of Modules	1
Input Power	35.7 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	3,040/85.1 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
EMI/RFI	Meets FCC Title 47, Part 15 Class B
Warranty	5-year Limited Warranty
Labels	cETLus Damp Location Listed Meets California Title 24 JA8-2016

P300244-009-30



Dimensions:

Width: 48 in
Height: 5-15/16 in
Depth: 4-3/16 in

White PMMA Diffuser
Width: 47-15/16 in
Height: 5-1/4 in



P300244-009-30

Dimming Notes:

P300244-009-30 is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

IDevices_IDEV0009

Lutron_Nova T VTELV-300

Lutron_Diva DVELV-300P

Lutron_Diva DVCL-253P

Lutron_Caseta Wireless

Lutron_Ariadni AYCL-153P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.