

## LED Linen

Flush-Mount Mounted • Damp Location Listed **PROGRESS LED**

### Description:

One-Light 11" LED Linen Glass Flush Mount

### Specifications:

- Etched White Linen Glass Bowl
- Dimmable to 10% brightness (See Dimming Notes)
- Unit covers a standard 4" recessed outlet box: 11.125 in W., 1.875 in ht., 11.125 in depth
- Mounting strap for outlet box included
- 6 in of wire supplied

### Performance:

Number of Modules	1
Input Power	21 W
Input Voltage	120 V
Input Frequency	50/60 Hz
Lumens/LPW (Source)	1,601/81 (LM-82)
Lumens/LPW (Delivered)	920/44 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	54000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Max. Operating Temp	25 °C
Warranty	5-year Limited Warranty
Labels	ETL Damp Location Listed
	Meets California Title 24 JA8-2016

# P350005-009-30



### Dimensions:

Diameter: 11 in  
Height: 4-5/8 in



**Dimming Notes:**

---

P350005-009-30 is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

**Dimming Controls:**

---

Lutron\_Nova T NTELV-300

Leviton\_SureSlide 6672

Leviton\_SureSlide 6674

Lutron\_Ariadni AYLV-600P

Lutron\_NTLV-600

Lutron\_Maestro MAELV-600

Lutron\_Nova N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.

**P350005-009-30**