

LED Linen

Flush-Mount Mounted • Damp Location Listed **PROGRESS LED**

Description:

One-Light 15" LED Linen Glass Flush Mount

Specifications:

- Etched White Linen Glass Bowl
- Dimmable to 10% brightness (See Dimming Notes)
- Unit covers a standard 4" recessed outlet box: 15.125 in W., 1.75 in ht., 15.125 in depth
- Mounting strap for outlet box included
- 6 in of wire supplied

Performance:

Number of Modules	1
Input Power	28 W
Input Voltage	120 V
Input Frequency	50/60 Hz
Lumens/LPW (Source)	2,409/88 (LM-82)
Lumens/LPW (Delivered)	1,389/50 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	54000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Max. Operating Temp	25 °C
Warranty	5-year Limited Warranty
Labels	ETL Damp Location Listed
	Meets California Title 24 JA8-2016

P350007-009-30



Dimensions:

Diameter: 15 in
Height: 5-7/8 in



Dimming Notes:

P350007-009-30 is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Lutron_Nova T NTELV-300

Leviton_SureSlide 6674

Lutron_Ariadni AYLV-600P

Lutron_NTLV-600

Lutron_Maestro MAELV-601

Leviton_Renoir II AWRMG-EAW

Lutron_Nova N-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.

P350007-009-30