

LED Flush Mount

Project:

Fixture Type:

Location:

Contact:

Flush-Mount Mounted • Damp Location Listed PROGRESS LED

Description:

One-Light 11" LED Flush Mount

Specifications:

- Etched Glass Diffuser
- Dimmable to 10% brightness (See Dimming Notes)
- Unit covers a standard 4" recessed outlet box: 11 in W., 1.3125 in ht., 11 in depth
- Mounting plate for outlet box included
- + 6 in of wire supplied

Performance:

Number of Modules	1
Input Power	17 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	1,347/76 (LM-79)
ССТ	3000 K
CRI	90+ CRI
Life (hours)	60000 (L70/TM-21)
EMI/RFI	Meets FCC Title 47, Part 15 Class B
Max. Operating Temp	30 °C
Warranty	5-year Limited Warranty
Labels	cCSAus Damp Location Listed
	Meets California Title 24 JA8-2016



P350053-009-30

Dimensions:

Diameter: 11 in Height: 4 in

Etched Glass Diffuser Length: 9-1/16 in Width: 9-1/16 in Height: 3-1/2 in





LED Flush Mount

Flush-Mount Mounted • Damp Location Listed PROGRESS LED

Dimming Notes:

P350053-009-30 is designed to be compatible with many NEMA SSL 7a Phase Cut (forward phase) dimmers as well as many ELV (reverse phase) controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Lutron_Diva DVELV-300P

Leviton_SureSlide 6674

Lutron_Diva DVCL-153P

Legrand_RHCL453

Eaton_SUL06P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.

P350053-009-30