

Project:		
Fixture Type:		
Location:		
Contact:		

Apogee

Flush-Mount Mounted • Damp Location Listed PROGRESS LED

Description:

Apogee Collection 21" LED Flush Mount

Specifications:

- · Etched Glass Shade
- Dimmable to 10% brightness (See Dimming Notes)
- Canopy covers a standard 4" recessed outlet box: 21 in W., 0.875 in ht., 21 in depth
- · Mounting strap for outlet box included
- 6 in of wire supplied

Performance:

Number of Modules	1	
Input Power	41 W	
Input Voltage	120-277 VAC	
Input Frequency	60 Hz	
Lumens/LPW (Delivered)	2,550/62 (LM-79)	
ССТ	3000 K	
CRI	90 CRI	
Life (hours)	58000 (L70/TM-21)	
EMI/RFI	FCC Title 47, Part 15, Class A	
Max. Operating Temp	30°C	
Warranty	5-year Limited Warranty	
Labels	cETLus Damp Location Listed	
	Meets California Title 24 JA8-2016	

P350071-009-30



Dimensions:

Diameter: 21 in Height: 4-1/2 in

Etched Glass Shade Width: 18-5/8 in Height: 3 in





Apogee

Flush-Mount Mounted • Damp Location Listed PROGRESS LED

Dimming Notes:

P350071-009-30

P350071-009-30 is designed to be compatible with many 0-10V controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Lutron_NFTV

Lutron_NTFTV

Lutron_DVTV

Leviton_AWSMT-7DW

Leviton_IP710

Lithonia_ISD BC

Pass & Seymour_CD4FB

Wattstopper_ADF-120277

Hunt Dimming_PS-010-120V

Hunt Dimming_PS010 277V

Lightolier Controls_MP1500FAM120

Lightolier Controls_ZP600FAM120

Synergy Lighting Controls_V2000FAMU

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.