

## Weaver LED

Flush-Mount Mounted • Damp Location Listed **PROGRESS LED**

### Description:

Weaver LED Collection Two-Light LED 16" Flush Mount

### Specifications:

- Off-White Linen Drum Shade
- Linen Glass Diffuser
- Dimmable to 10% brightness (See Dimming Notes)
- Ceiling pan covers a standard 4" recessed outlet box: 16 in W., 0.8125 in ht., 16 in depth
- Mounting strap for outlet box included
- 6 in of wire supplied

### Performance:

Number of Modules	2
Input Power	17 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Source)	1,211/71.2 (LM-82)
Lumens/LPW (Delivered)	1,178/36 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	60000 (L70/TM-21)
EMI/RFI	Meets FCC Title 47, Part 15 Class B
Max. Operating Temp	30 °C
Warranty	5-year Limited Warranty
Labels	cCSAus Damp Location Listed

## P3611-0930K9



### Dimensions:

Diameter: 16 in  
Height: 4 in

Off-White Linen Drum Shade  
Width: 15-7/8 in  
Height: 1-3/4 in

Linen Glass Diffuser  
Width: 15-5/16 in  
Height: 1-3/8 in



# P3611-0930K9

## Dimming Notes:

---

P3611-0930K9 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

## Dimming Controls:

---

Lutron\_Nova T NTELV-300

Lutron\_Vierti VTELV-600

Lutron\_Maestro MAELV-600

Lutron\_spacer/system SPSELV-600

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.