

Project:			
Fixture Type:			
Location:			
Contact:			

LED Strips

Wall or ceiling Mounted • Damp Location Listed PROGRESS LED

Description:

Four-Foot LED Strip Light

Specifications:

- · White Polycarbonate Diffuser
- · Dimmable to 10% brightness (See Dimming Notes)
- $\boldsymbol{\cdot}$ Mounting backplate for outlet box included
- 6 in of wire supplied

Performance:

Number of Modules	1
Input Power	40 W
Input Voltage	120 V
Input Frequency	60 Hz
Lumens/LPW (Delivered)	3,200/80 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
EMI/RFI	Meets FCC Title 47, Part 15 Class B
Warranty	5-year Limited Warranty
Labels	cCSAus Damp Location Listed
	Meets California Title 24 JA8-2016

D	77		01	 -0	Z		_7	
	/ 3	V	VI		9	V	-5	U

Dimensions:

Length: 47-5/16 in Width: 2-1/8 in Height: 2-7/16 in Depth: 2-1/8 in

		2.392 in
•	- 47.283 in	



LED Strips

Wall or ceiling Mounted • Damp Location Listed PROGRESS LED

P730001-030-30

Dimming Notes:

P730001-030-30 is designed to be compatible with many ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

Dimming Controls:

Lutron_Diva DVELV-300P

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.