

## Everlume

Ceiling Mounted • Damp Location Listed **PROGRESS LED**

### Description:

Everlume LED 24-inch Satin White Modern Style Linear Ceiling Panel Light

### Specifications:

- Dimmable to 10% brightness (See Dimming Notes)
- Mounting backplate for outlet box included
- 6 in of wire supplied

### Performance:


Number of Modules	1
Input Power	20.6 W
Input Voltage	120 VAC
Input Frequency	60 Hz
Lumens/LPW (Delivered)	1,581/76 (LM-79)
CCT	3000 K
CRI	90 CRI
Life (hours)	50000 (L70/TM-21)
EMI/RFI	FCC Title 47, Part 15, Class B
Warranty	5-year Limited Warranty
Labels	cCSAus Damp Location Listed
	Meets California Title 24 JA8-2016

# P810032-028-30



### Dimensions:

Width: 23-3/4 in  
Depth: 11-15/16 in  
Height: 1-3/16 in



### Dimming Notes:

---

P810032-028-30 is designed to be compatible with many Triac/Forward Phase ELV/Reverse Phase controls.

The following is a partial list of known compatible dimmer controls.

### Dimming Controls:

---

Eaton AAL06

Leviton\_Trimatron 6681

Leviton IPI06-1LZ

Leviton 6674

Lutron NTEVL-300

Lutron DVELV-300P

Lutron DVCL-253P

Lutron AYCL-153P

Lutron TGCL-153-PH-WH

Lutron MACL-153M

Dimming capabilities will vary depending on the dimmer control, load, and circuit installation.

Always refer to dimmer manufacturer instructions or a controls specialist for specific requirements.

Dimmer control brand names where identified above are trade names or registered trademarks of each respective company.

# P810032-028-30