



Project / Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S11606** - 24 watt LED Direct Wire Downlight; Edge-lit; 8 inch; 3000K; 120 volt; Dimmable; Round; Remote Driver



### GENERAL

Company	SATCO
EA Height	9.41
EA Width	1.81
EA Length	9.41
Bulb Included	Integrated
Diameter	8.88
Material	Aluminum
Fixture Type	Remote Driver LED Downlight
Status	Discontinued
CCT Selectable	No
Wattage Selectable	No
Finish Family	White
Additional Info	Integrated j-box for direct wire installation
Amps	0.200A
Has Camera	No
IOT Enabled	No
Lens Finish	Frost
Lens Material	Poly methyl methacrylate (PMMA)
Power Factor	0.99
SDS Class	LED_Lamp
Sloped Ceiling Compatible	No
Indoor Outdoor	Indoor
Product Technology	LED
Incandescent Equivalent	120W

### ELECTRICAL

CCT (Kelvin Temp)	3000K
Dimmable	Yes-Dimmable
Hours Rated	50000
Beam Angle (degree)	108
Color Temp	Warm White
CRI	90+
Dimming Type	120V only, Phase cut
Operating Temp	-4F to +113F (-20C to +45C)
Lumens	1800L
Volts	120v
Watts	24W

### PHYSICAL

Lamp Base	Integrated
Finish	WHITE
ANSI Base	Integrated
Lamp Type	Integrated LED
Fixture Shape	Round

### ADDITIONAL INFO

Warranty	5-Years
----------	---------

### PACKAGING

UPC	045923116063
Case Cube	1.3813
Case Height	10.24
Case Length	23.31
Case Quantity	12
Case UPC	10045923116060
Case Weight	27.92
Case Width	10.0
EA Cube	0.0928
EA Height	9.41
EA Length	9.41
EA Quantity	1
EA Weight	1.99
EA Width	1.81
Pack Type	Box
Web Height	0.94
Web Width	8.88

### COMPLIANCE

Air Tight	Yes
CA Prop 65	Lead
FCC Compliant	Yes
IC Rated	Yes
Location Rating	Wet
ROHS Compliant	Yes
Safety Listing	cETLus - Listed
California Ban	California T24 Listed
UL Application	Ceiling
DLC Approved	No
Energy Star Certified	No
Title 20	Exempt
T24 Compliant	Yes