



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11867R1 - 13 Watt LED; Fire Rated 6 Inch Direct Wire Slim Fit Step Baffle Downlight; Round Shape; White Finish; CCT Selectable; 120 Volts; Dimmable

- Air Tight
- Flicker Free
- CCT Selectable
- IC Rated



ELECTRICAL

Technology:	LED
Watts:	13W
Volts:	120V
Lumens:	1100L
CRI:	90+
CCT (Kelvins):	27K/30K/35K/40K/50K - Warm White to Natural Light
Beam Spread :	110
Hours Rated:	50000
Dimmable:	Yes-Dimmable - 120V only
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Phase cut
Incandescent Equivalent :	75W
Operating Temperature :	-20C (-4F) to +40C (+104F)
Replaceable Light Source :	No
Connection:	Hardwire
THD:	<20%
Power Factor :	>0.9
Voltage Type:	AC Only
Warranty:	5-Years

PACKAGING

Each UPC:	045923410192
Each Quantity:	1
Each Dimensions:	7.87 x 2.76 x 6.93

PHYSICAL

Finish:	White / Red
Lens Finish:	Frosted
Lens Material:	Polycarbonate (PC)
Dimensions:	H:0.88" DIA:6.79"
Weight (Lbs.):	1.39
Material:	Steel

INSTALLATION

Ceiling Aperture:	5.875 in. Cutout
Max Drywall Thickness:	1.181 in.
Sloped Ceiling Compatible:	No

COMPLIANCE

Safety Listing:	cULus - Certified
Location Rating:	Wet
Indoor/Outdoor:	Indoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	4479603
Energy Star Lamp Category:	Downlight Recessed
CA Prop 65:	Lead
BAA Compliant:	No
Vapor Tight Fixture Rated:	No
ADA Compliant:	No
Closet Rated:	Yes
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
Restrictions:	No Restrictions

ACCESSORIES

	80-866	6-Inch Asymmetric New Construction Recessed Downlight Mounting Plate; Flat
	80-867	Universal New Construction Recessed Downlight Mounting Plate; Flat; 3,5-Inch; 4-Inch; 6-Inch; 8-Inch
	80-944	New Construction Mounting Plate with Hanger Bars for T-Grid or Stud/ Joist mounting of 6-inch Recessed Downlights: Up to 6.25-inch hole diameter
	80-947	6" Goof Ring for Remote Driver Installation
	80-973	Emergency Driver Enclosure; For use with S8000 and S8002
	80-985	6 FOOT REMOTE DRIVER 3-PIN EXT
	80-987	Emergency Remote Test Switch; Single Gang Plate; White Finish
	80-997	Downlight Hanger Bar Kit; For Asymmetrical Plates; New Construction
	S8000	5 Watt LED Emergency Driver; 120-277 Volts
	S8002	10 Watt LED Emergency Driver; 120-277 Volt
