



Project/Job Name: \_\_\_\_\_

Location: \_\_\_\_\_

Fixture Type: \_\_\_\_\_

Notes: \_\_\_\_\_

**S11868R1** - 10 Watt LED; Fire Rated 4 Inch; Direct Wire Slim Fit Flat Face Downlight; Round Shape; White Finish; CCT Selectable; 120-277 Volts; 0-10V Dimmable

- Air Tight
- Flicker Free
- CCT Selectable
- IC Rated



## ELECTRICAL

Technology:	LED
Watts:	10W
Volts:	120V-277V
Lumens:	820L
CRI:	90+
CCT (Kelvins):	27K/30K/35K/40K/50K - Warm White to Natural Light
Beam Spread :	110
Hours Rated:	50000
Dimmable:	Yes-Dimmable - 0-10V Dimming
Dimmable Down To %:	100 to 10 percent
Incandescent Equivalent :	60W
Operating Temperature :	-20C (-4F) to +40C (+104F)
Replaceable Light Source :	No
Connection:	Hardwire
THD:	<20%
Power Factor :	>0.9
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

## PACKAGING

Each UPC:	045923410208
Each Quantity:	1
Each Dimensions:	5.83 x 3.70 x 7.48

## PHYSICAL

Finish:	White / Red
Lens Finish:	Frosted
Lens Material:	Polycarbonate (PC)
Dimensions:	H:0.88" DIA:4.74"
Weight (Lbs.):	1.49
Material:	Steel

## INSTALLATION

Ceiling Aperture:	3.875 in. Cutout
Max Drywall Thickness:	1.181 in.
Sloped Ceiling Compatible:	No

## COMPLIANCE

Safety Listing:	cULus - Certified
Location Rating:	Wet
Indoor/Outdoor:	Indoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	4479604
Energy Star Lamp Category:	Downlight Recessed
CA Prop 65:	Lead
BAA Compliant:	No
Vapor Tight Fixture Rated:	No
ADA Compliant:	No
Closet Rated:	Yes
FCC Compliant:	Yes
NSF Approved:	No
RoHS Compliant:	Yes
Restrictions:	No Restrictions

**ACCESSORIES**

	<b>80-865</b>	4-Inch Asymmetric New Construction Recessed Downlight Mounting Plate; Flat
	<b>80-867</b>	Universal New Construction Recessed Downlight Mounting Plate; Flat; 3,5-Inch; 4-Inch; 6-Inch; 8-Inch
	<b>80-943</b>	New Construction Mounting Plate with Hanger Bars for T-Grid or Stud/ Joist mounting of 4-inch Recessed Downlights; Up to 4.25-inch hole diameter
	<b>80-946</b>	4" Goof Ring for Remote Driver Installation
	<b>80-950</b>	New Construction Mounting Plate for Stud/ Joist mounting of 4-inch Recessed Downlights; Up to 4.563-inch hole diameter
	<b>80-973</b>	Emergency Driver Enclosure; For use with S8000 and S8002
	<b>80-985</b>	6 FOOT REMOTE DRIVER 3-PIN EXT
	<b>80-987</b>	Emergency Remote Test Switch; Single Gang Plate; White Finish
	<b>80-997</b>	Downlight Hanger Bar Kit; For Asymmetrical Plates; New Construction
	<b>S8000</b>	5 Watt LED Emergency Driver; 120-277 Volts
	<b>S8002</b>	10 Watt LED Emergency Driver; 120-277 Volt