



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11875 - 12 Watt; LED Direct Wire Downlight; Edge-lit; 6 inch; CCT Selectable; 120 volt; Dimmable; Round; Remote Driver; Black Finish

- Air Tight
- IC Rated
- CCT Selectable



ELECTRICAL

Technology:	LED
Watts:	12W
Volts:	120V
Lumens:	900L
CRI:	90
Rg Value :	51
CCT (Kelvins):	2700K/3000K/3500K/4000K/5000K
Color Description:	Warm to Cool White
Beam Spread :	108
Hours Rated:	50000
Dimmable:	Yes-Dimmable
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Phase cut
Incandescent Equivalent :	65W
Operating Temperature :	-20C (-4F) to +45C (+113F)
Replaceable Light Source :	No
Number of LEDs :	72
Connection:	Direct Wired
THD:	<20%
Power Factor :	>0.9
Warranty:	5 Year Limited - Fixtures

PACKAGING

Each UPC:	045923311406
Each Quantity:	1
Each Dimensions:	7.13 x 2.13 x 7.13
Case UPC:	10045923311403
Case Quantity:	12
Case Dimensions:	15.63 x 13.94 x 8.11

PHYSICAL

Finish:	Black
Lens Finish:	Frost
Lens Material:	Poly methyl methacrylate (PMMA)
Finish Family:	Black
Dimensions:	H:0.90" DIA:6.78"
Weight (Lbs.):	1
Material:	Aluminum

COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Wet
Indoor/Outdoor:	Indoor; Outdoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	ESID-2732792
Energy Star Lamp Category:	Downlight Recessed
UL/ETL Standard:	UL 1598; CSA-C22.2 No. 250.0
CA Prop 65:	Lead
FCC Compliant:	Yes
IP Rating:	IP20
RoHS Compliant:	Yes
SDS Class:	LED_Lamp
Restrictions:	No Restrictions

ACCESSORIES



80-944

New Construction Mounting Plate with Hanger Bars for T-Grid or Stud/ Joist mounting of 6-inch Recessed Downlights: Up to 6.25-inch hole diameter



80-949

6 FOOT REMOTE DRIVER 1-PIN EXT



80-973

Emergency Driver Enclosure; For use with S8000 and S8002



80-987

Emergency Remote Test Switch; Single Gang Plate; White Finish



86-216

Temporary work light; LED; For use with remote drivers; Low voltage 10W/12W/24W; 3000K; 12 Volts



S8000

5 Watt LED Emergency Driver; 120-277 Volts



S8002

10 Watt LED Emergency Driver; 120-277 Volt



S11875 - 12 Watt; LED Direct Wire Downlight; Edge-lit; 6 inch; CCT Selectable; 120 volt; Dimmable; Round; Remote Driver; Black Finish

DIMMER COMPATIBILITY

Leviton	6672
Leviton	6674
Satco	86/103
Legrand	ADTP703TU
Lutron	AYCL-153P
Lutron	AYCL-253P
Lutron	CTCL-153P
Eaton	DAL06P-C2
Leviton	DDMX1
Leviton	DG6HD
Leviton	DH6HD
Leviton	DL6HD
Leviton	DSE06-10Z
Leviton	DSL06
Leviton	DSL06-1LZ
Leviton	DSM10
Eaton	DUL06P-C2
Lutron	DVCL-153P
Lutron	DVCL-253P
Leviton	DW6HD
Leviton	DZ6HD
Lutron	HQRA-PRO
Lutron	HQRD-10D
Lutron	HQRD-10NBD
Lutron	HQRD-6ND
Lutron	HQRD-HN6BRL

Lutron	HQRD-PRO
Lutron	HRST-PRO-N
Leviton	IPLo6
Lutron	LECL-153P
Lutron	MACL-153M
Lutron	MACL-LFQ
Lutron	MSCL-OP153M
Lutron	NTCL-250
Lutron	PD-10NXD
Lutron	PD-6WCL
Lutron	RCL-153PNL
Eaton	RF9640-ND
Legrand	RH703PTUTC
Legrand	RHCL450PTC
Leviton	RNL06-10Z
Lutron	RRD-10D
Lutron	RRD-6CL
Lutron	RRD-6ND
Lutron	RRD-H6BRL
Lutron	RRD-PRO
Lutron	RRST-PRO-N
Eaton	SALo6P
Lutron	SCL-153P
Lutron	ST-PRO-N
Lutron	STCL-153M
Eaton	SUF7
Eaton	TALo6P-C2
Lutron	TGCL-153PH

Leviton	TSL06
Leviton	TSM10
Lutron	TTCL-100H
Eaton	VSUL06D