



Project / Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S11881 - 15 Watt LED; Fire Rated; 6 Inch Direct Wire Directional Downlight; Round Shape; White Finish; CCT Selectable; Dimmable; 120 Volts



GENERAL

| | |
|---------------------------|--|
| Company | SATCO |
| EA Height | 8.27 |
| EA Width | 3.94 |
| EA Length | 8.19 |
| Bulb Included | Integrated |
| Diameter | 7.48 |
| Material | Aluminum |
| Fixture Type | Remote Driver LED Downlight |
| Product Notes | Rotation Angle 360 degrees; Tilt Angle 80 degrees |
| Status | Active |
| Style | Utility |
| Surge Protection | Built-in surge protection - 1.5KV |
| Total Harmonic Distortion | <30% |
| CCT Selectable | Yes |
| Wattage Selectable | No |
| Can Size | 6 in. |
| Finish Family | White |
| Additional Info | 2HR Fire Rated: Tested to comply with UL 263/ASTM E119/CAN-ULC S101-07 |
| Amps | 0.14A |
| Has Camera | No |
| IOT Enabled | No |
| Lens Finish | Frost |
| Lens Material | Poly methyl methacrylate (PMMA) |
| Power Factor | >0.9 |
| SDS Class | LED_Lamp |
| Sloped Ceiling Compatible | Yes |
| Indoor Outdoor | Indoor |
| Product Technology | LED |
| Fixture Lamp Count | 1 |
| Incandescent Equivalent | 75W |

ELECTRICAL

| | |
|---------------------|-------------------------------|
| CCT (Kelvin Temp) | 2700K/3000K/3500K/4000K/5000K |
| Dimmable | Yes-Dimmable |
| Hours Rated | 50000 |
| Beam Angle (degree) | 40 |
| Color Temp | Warm White to Natural Light |
| CRI | 90+ |
| Dimming Type | 120V only, Phase cut |
| Operating Frequency | 60Hz |
| Operating Temp | -4F to +104F (-20C to +40C) |
| Lumens | 1280L |
| Volts | 120v |
| Watts | 15W |

PHYSICAL

| | |
|---------------|----------------|
| Lamp Base | Integrated |
| Finish | WHITE |
| ANSI Base | Integrated |
| Lamp Type | Integrated LED |
| Fixture Shape | Round |

ADDITIONAL INFO

| | |
|----------|---------|
| Warranty | 5-Years |
|----------|---------|

PACKAGING

| | |
|---------------|----------------|
| UPC | 045923118814 |
| Case Cube | 2.1874 |
| Case Height | 17.32 |
| Case Length | 17.32 |
| Case Quantity | 12 |
| Case UPC | 10045923118811 |
| Case Weight | 24.91 |
| Case Width | 12.6 |
| EA Cube | 0.1544 |
| EA Height | 8.27 |
| EA Length | 8.19 |
| EA Quantity | 1 |
| EA Weight | 1.87 |
| EA Width | 3.94 |
| Pack Type | Box |
| Web Height | 2.17 |
| Web Width | 7.48 |

COMPLIANCE

| | |
|-----------------------|-----------------------|
| Air Tight | Yes |
| CA Prop 65 | Lead |
| FCC Compliant | Yes |
| IC Rated | Yes |
| Location Rating | Wet |
| ROHS Compliant | Yes |
| Safety Listing | cETLus - Listed |
| California Ban | California T24 Listed |
| UL Application | Covered Ceiling Mount |
| DLC Approved | No |
| Energy Star Certified | No |
| Title 20 | Exempt |
| T24 Compliant | Yes |