



Project/Job Name: _____

Location: _____

Fixture Type: _____

Notes: _____

S21609 - 18.5W Field Selectable LED 6-Inch Commercial Downlight; Dual Dimming; Square; 120-347 Volt

- Wattage Selectable
- CCT Selectable
- IC Rated
- Air Tight
- Has Driver



ELECTRICAL

Technology:	LED
Watts:	18.5W/15.7W/13.2W
Volts:	120V-347V
Lumens:	2200L/1800L/1400L
CRI:	90+
CCT (Kelvins):	27K/30K/35K/40K/50K - Warm White to Natural Light
Beam Spread :	85
Hours Rated:	50000
Dimmable:	Yes-Dimmable - Phase Cut at 120V/0-10V at 120-347V
Dimmable Down To %:	100 to 10 percent
Dimming Type :	Dual Dimming
Incandescent Equivalent :	100W
Operating Temperature :	-20C (-4F) to +40C (+104F)
Replaceable Light Source :	No
Connection:	Hardwire
THD:	<30%
Power Factor :	>0.9
Voltage Type:	AC Only; Range Voltage
Warranty:	5-Years

PACKAGING

Each UPC:	045923411243
Each Quantity:	1
Each Dimensions:	7.87 x 3.94 x 9.06

INFO

Specification Note:	Default CCT setting is 3000K. Default wattage setting is 18.5W.
---------------------	---

PHYSICAL

Finish:	White
Lens Material:	Polycarbonate (PC)
Dimensions:	L:7.40" W:7.40" H:3.43"
Weight (Lbs.):	1.15
Material:	Aluminum

INSTALLATION

Sloped Ceiling Compatible:	No
----------------------------	----

COMPLIANCE

Safety Listing:	cETLus - Listed
Location Rating:	Damp
Indoor/Outdoor:	Indoor
Energy Star Qualified:	Yes
Energy Star Unique ID:	4481354
Energy Star Lamp Category:	Downlight Recessed
CA Prop 65:	Lead
BAA Compliant:	No
ADA Compliant:	No
Closet Rated:	No
FCC Compliant:	Yes
IP Rating:	IP20
NSF Approved:	No
RoHS Compliant:	Yes
Restrictions:	No Restrictions

ACCESSORIES

**80-959**Rough-In Mounting Plate for 4/6/8 or 10 in. Commercial Downlight Fixtures

**S13551**6" Flat Goof Ring for Commercial Downlights, Square, White Finish, 10.00 square outer, 6.00 square inner, 0.032 Thick.

**S21665**6-Inch Square Trim for LED Commercial Downlight; Black Finish

**S21666**6-Inch Square Trim for LED Commercial Downlight; Bronze Finish

**S21667**6-Inch Square Trim for LED Commercial Downlight; Silver Finish
