SATCO NUVO

Project Name

Location

Prepared By



SATCO S28713

45W/LED/HID/5K/277-347V/EX39

Notes

www] 03-22-2021 04:50:

General	
Status	Active
Watts	45
Incandescent Equivalent	300
Fluorescent Equivalent	65
HID Equivalent	175
Volts	277V-347V
Shape	Corncob
Base	Mogul Extended
ANSI Base	EX39
Finish	Clear
CCT (Kelvin)	5000
Temperature	Natural Light
CRI	80+
Lumens	6000
Beam Spread	300
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	Corncob
Technology	LED
Min Compartment Size	Length: 17.3 in. Width: 9.25 in. Depth: 9.25 in.
Ballasting Requirements	Ballast Bypass-Direct wire only 277-347V
Electrical	
	AC 250-380V
Working Voltage	AC 250-380V 50-60 Hz
Working Voltage Operating Frequency	50-60 Hz
Working Voltage Operating Frequency Power Factor	50-60 Hz >0.88
Working Voltage Operating Frequency Power Factor Burning Position	50-60 Hz >0.88 Up or Down Operation Only Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature
Working Voltage Operating Frequency Power Factor Burning Position Thermal Management	50-60 Hz >0.88 Up or Down Operation Only Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -20C (-4F) to a maximum of +65C
Working Voltage Operating Frequency Power Factor Burning Position Thermal Management Operating Temperature	50-60 Hz >0.88 Up or Down Operation Only Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -20C (-4F) to a maximum of +65C
Working Voltage Operating Frequency Power Factor Burning Position Thermal Management Operating Temperature Physical	50-60 Hz >0.88 Up or Down Operation Only Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -20C (-4F) to a maximum of +65C (+149F)
Working Voltage Operating Frequency Power Factor Burning Position Thermal Management Operating Temperature Physical MOL	50-60 Hz >0.88 Up or Down Operation Only Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -20C (-4F) to a maximum of +65C (+149F)
Working Voltage Operating Frequency Power Factor Burning Position Thermal Management Operating Temperature Physical MOL MOD	50-60 Hz >0.88 Up or Down Operation Only Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -20C (-4F) to a maximum of +65C (+149F)
Working Voltage Operating Frequency Power Factor Burning Position Thermal Management Operating Temperature Physical MOL MOD Lens Finish	50-60 Hz >0.88 Up or Down Operation Only Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -20C (-4F) to a maximum of +65C (+149F) 10.35 3.66 Clear
Working Voltage Operating Frequency Power Factor Burning Position Thermal Management Operating Temperature Physical MOL MOD Lens Finish Housing Color	50-60 Hz >0.88 Up or Down Operation Only Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -20C (-4F) to a maximum of +65C (+149F) 10.35 3.66 Clear White
Working Voltage Operating Frequency Power Factor Burning Position Thermal Management Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.)	50-60 Hz >0.88 Up or Down Operation Only Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -20C (-4F) to a maximum of +65C (+149F) 10.35 3.66 Clear White
Working Voltage Operating Frequency Power Factor Burning Position Thermal Management Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information	50-60 Hz >0.88 Up or Down Operation Only Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -20C (-4F) to a maximum of +65C (+149F) 10.35 3.66 Clear White 2.15 Replaces HID, CFL, and Incandescent; UL approved for totally enclosed fixtures; Emits no
Working Voltage Operating Frequency Power Factor Burning Position Thermal Management Operating Temperature Physical MOL MOD Lens Finish Housing Color Weight (lb.) Additional Information	50-60 Hz >0.88 Up or Down Operation Only Hi-PRO lamps are manufactured with a new Thermal Management circuit design (Temperature Control).I -20C (-4F) to a maximum of +65C (+149F) 10.35 3.66 Clear White 2.15 Replaces HID, CFL, and Incandescent; UL approved for totally enclosed fixtures; Emits no UV light / Contains no Mercury (Hg)

Warranty







5 Year Limited - Hi-Pro



Compliance	
Safety Listing	cULus
Location Rating	Damp
Energy Star	No
DLC Approved	Yes
DLC ID	PLFWZJA3QGO4
California Status	Lawful for sale in California
Nevada Status	Lawful for sale in Nevada
RoHS Compliant	Yes
SDS Sheet	LED_Lamp







