

Project Name

Location

Prepared By



Notes

[www] 03-22-2021 04:50:55

General

Status	Active
Watts	9
Fluorescent Equivalent	See Notes
Volts	120V-277V
Ballast Type	Type B
Shape	PL
Base	2-Pin
ANSI Base	G24d
Finish	Frosted
CCT (Kelvin)	2700
Temperature	Warm White
CRI	82
Lumens	900
Beam Spread	120
Dimmable	Non-Dimmable
Hours Rated	50000
Lamp Type	PL
Burning Position	Horizontal Operation
Technology	LED

Electrical

Ballasting Requirements	Ballast Bypass-Direct wire only 100-277V
Operating Frequency	50/60 Hz
Operating Temperature	-20C (-4F) to a maximum of +45C (+113F)

Physical

MOL	6.63
MOD	1.09

Additional Information

Additional Info	In G24d (2-pin) sockets replaces 18 and 26 watt CFLs; In G24q (4-pin) sockets replaces 13; 18; and 26 watt CFLs
Installation Notes	2-pin LED lamps work in both 2-pin (magnetic) and 4-pin (electronic) sockets.
Warranty	5 Year Limited - 10 hr per day

Compliance

Safety Listing	cULus Classified
Location Rating	Damp
Energy Star	No
California Status	Lawful for sale in California
Nevada Status	Lawful for sale in Nevada
RoHS Compliant	Yes
SDS Sheet	LED_Lamp

