



S9930

15T8U6/LED/22.5-830/BP
 15 watt T8 U-Bend LED; Medium bi-pin base; 3000K; 50000 average rated hours; 1700 lumens



Features

- No ballast or external driver required
- Direct wire 120-277V line voltage*
- Single-ended wiring
- All glass tube
- NSF Approved

* Install only in non-shunted lampholders

S9930

Item Number	UPC	Watts	Lamp Shape	Base	ANSI Base	Lamp Code	Dimmable/Non-Dimmable
S9930	045923099304	15	T8	Medium Bi-Pin	2G13	15T8U6/LED/22.5-830/BP	Non-Dimmable
Finish	MOL In Inches	MOD In Inches	Leg Spacing	Initial Lumens	Average Rated Hours	Kelvin Temp	Color
White	22.5"	7.00"	6"	1700	50000	3000	Warm White
CRI	Beam Spread Deg	Operating Temperature	Pack	Package Type	DLC ID:	RoHS Compliant	UL or ETL Listed
82	220	-20C (-4F) to a maximum of +45C (+113F)	12	Box	PJM4D71J DLC Search	Yes	Yes
UL Classification						Warranty	
cULus Classified - Damp Location Rated						5 Year Limited	



National Toll-Free:
800.43.SATCO
(800.437.2826)
www.satco.com

Distribution Centers:
New York, Florida, Texas,
Washington, California,
Puerto Rico

Corporate Offices:
110 Heartland Blvd.,
Brentwood, NY 11717
800.437.2826 631.243.2022
Fax 631.243.2027

