

Project:

Thin-Line LED Wall Bar

SKU: 2812.16-8

One of our best selling families, Thin-Line is a system of minimally scaled LED wall bars, [indirect light wall bars](#), and [pendants](#). Thin-Line is offered in a variety of lengths, finishes, and lighting configurations. One-sided configurations direct light in a single direction, and can be mounted in an upright or downlight orientation. Two-sided configurations direct light both up and down.

Learn more: <https://sonnemanlight.com/thin-line-led-wall-bar>



Dimensions

Height	1"
Width	96"
Extends	3.5"
Minimum Extension	3.5"
Maximum Extension	3.5"
Size	8' Two-Sided
Canopy/Backplate/Base Width	1"
Canopy/Backplate/Base Height	1"

Electrical Specs

Bulb(s) Included?	Yes
Bulb 1 Type	Integral LED
Total LED, Bulb or Socket Count	2
Input Voltage	120VAC
Wattage	94
Initial Lumens	6240
Delivered Lumens	3590
Kelvin	3000K
CRI	90
Power Supply Type	Driver
Power Supply Quantity	2
Power Supply Location	Remote
Dimming Type	TRIAC/ELV

Installation

Installation	Licensed electrician required
Installation Orientation	Any Orientation

Diffuser(s), Shade(s) and Lens(es)

Diffuser Type	Optical Acrylic
---------------	-----------------

Shipping

Carton 1 L x W x H	99" X 7" X 4"
Carton 1 Gross Weight	8 LBS

General Listings

Color/Finish	Bright Satin Aluminum (.16)
Features	Damp Rated
Certification	C-ETL-US

Available Finishes

Available Finishes	Bright Satin Aluminum (.16), Satin Black (.25), Satin White (.03)
--------------------	---

Available Color Temperatures

Available Color Temperatures	2700K, 3000K, 3500K
------------------------------	---------------------