

Project:

Tela LED Pendant Spec Sheet

SKU: 3121.03 Learn more at: https://sonnemanlight.com/tela-led-pendant

Description: Elegantly draped along the axis of a tubular LED source, this flowing reflector directs the linear illumination downward. Tela can be used singularly or in an end-to-end linear configuration of multiple lengths as desired. Its sophisticated simplicity brings a sculptural flowing rhythm along a surface or within a linear space.

3.5"

40"

3.75"

Adjustable Cord/Cable

Single Pendant

0.5

4.5"

6'

Type #:

Dimensions

Height: Width:	
Length: Canopy/Backplate/Base: Hanging Details:	

Size:

Canopy/Backplate/Base Height:

Electrical Specs

Bulb(s) Included?: Bulb 1 Type: Bulb Quantity: Input Voltage: Wattage: Initial Lumens: Delivered Lumens: Color Temperature: CRI: Power Supply Type: Power Supply Quantity: Power Supply Quantity: Power Supply Location: Dimming Type: Bulb Max Wattage: Yes Integral LED 1 120VAC 15 2100 1470 3000K 90 Driver 1 Outlet Box TRIAC/ELV 15

Installation

Installation:
Sloped Ceiling Compatible?:
Minimum Hanging Height: Maximum Hanging Height:

Shipping

Carton 1 L x W x H: 49" X 8" X 8" Carton 1 Gross Weight: 7 LBS

Shade

Shade 1 Material:

Metal

Available Finishes

Available Finishes: Dove Gray (.18), Satin Black (.25), Satin White (.03)

General Listings

Features: Certification: Color/Finish:

Dark Sky Friendly:

Damp Rated C-ETL-US Satin White (.03) N





Licensed electrician required Adapter Available 5" 77"