


Project:

Belle Flare Short LED Bell
Pendant

SKU: 3531.14

Unmistakably modern, the pristine curved Belle Flare Pendant directs LED light downward through reflective radiance within the dome shade while subtly reflecting light upward through the flared trim at the top of the dome. Scaled for residential, hospitality and commercial settings for an enduring modern presence.

Learn more: <https://sonnemanlight.com/belle-flare-pendant>



Dimensions

Height	11.5"
Diameter	18"
Hanging Details	20' Adjustable Cord
Size	Short
Canopy/Backplate/Base	4.5"
Canopy/Backplate/Base Height	0.5"

Electrical Specs

Bulb(s) Included?	Yes
Bulb 1 Type	Integral LED
Total LED, Bulb or Socket Count	1
Input Voltage	120-277VAC
Initial Lumens	1680
Kelvin	3000K
CRI	90
Power Supply Type	Driver
Power Supply Quantity	1
Power Supply Location	Outlet Box
Dimming Type	TRIAC/ELV/0-10V

Installation

Installation	Licensed electrician required
Sloped Ceiling Compatible?	Not Compatible
Cord Length	20 ft
Minimum Hanging Height	12.5"
Maximum Hanging Height	251.5"

Diffuser(s), Shade(s) and Lens(es)

Diffuser Type	Metal
Shade Color	Brass Finish

General Listings

Color/Finish	Brass Finish (.14)
Features	Damp Rated
Certification	C-ETL-US

Available Finishes

Available Finishes	Brass Finish (.14), Satin Black (.25), Satin White (.03)
--------------------	--

Available Color Temperatures

Available Color Temperatures	3000k
------------------------------	-------

Options In This Family

SKU	Size	Wattage	CRI	Delivered Lumens
3531.XX	Short		90	
3535.XX	Tall		90	