


TUBE ARCHITECTURAL DS-WS05

LED Wall Mounts

WAC LIGHTING®



Fixture Type:

Catalog Number:

Project:

Location:

PRODUCT DESCRIPTION

The latest energy efficient LED technology in an appealing cylindrical profile delivers accent and wall wash lighting. Comes in various light distribution and beam angle options.

FEATURES

- High performance exterior rated LED wall mount light
- Fixture can install upside down to alter light distribution
- Solid aluminum construction
- 5 year warranty

SPECIFICATIONS

Input:	Universal voltage 120V - 277VAC, 50/60Hz
Dimming:	Electronic low voltage (ELV) : 100% - 5% 0-10V: 100% - 1%
Light Source:	High output 3 Step Mac Adam Ellipse COB Rated life of 60,000 hours at L70
Finish:	Electrostatically powder coated, white, black, bronze and graphite
Standards:	IP65 rated, ETL & cETL wet location listed, Title 24 JA8 Compliant
Operating Temp:	-13°F to 122°F (-25°C to 50°C)

ORDERING NUMBER

Diameter	Watt	Beam	Beam Angle	Color Temp	CRI	Reference Lumen	Output ¹ CBCP	Efficacy (lm/w)	Light Distribution	Finish	
DS-WS05	5" 25W	S Straight up or down	16°	927S	2700K	90	1825	10050	73		BK Black WT White BZ Bronze GH Graphite
				27S	2700K	85	2190	12057	88		
				930S	3000K	90	1895	10427	76		
				30S	3000K	85	2300	12644	92		
				35S	3500K	85	2350	12937	94		
				40S	4000K	85	2375	13062	95		
		N Straight up or down	25°	927S	2700K	90	1810	5280	72		
				27S	2700K	85	2170	6335	87		
				930S	3000K	90	1880	5478	75		
				30S	3000K	85	2275	6643	91		
				35S	3500K	85	2330	6797	93		
				40S	4000K	85	2350	6863	94		
		F Straight up or down	33°	927S	2700K	90	1900	4515	76		
				27S	2700K	85	2280	5417	91		
				930S	3000K	90	1970	4685	79		
30S	3000K			85	2390	5681	96				
35S	3500K			85	2445	5812	98				
40S	4000K			85	2470	5870	99				
F Away from the wall	N/A	927A	2700K	90	2000	N/A	80				
		27A	2700K	85	2400	N/A	96				
		930A	3000K	90	2075	N/A	83				
		30A	3000K	85	2520	N/A	101				
		35A	3500K	85	2575	N/A	103				
		40A	4000K	85	2600	N/A	104				
F Towards the wall	N/A	927B	2700K	90	2000	N/A	80				
		27B	2700K	85	2400	N/A	96				
		930B	3000K	90	2075	N/A	83				
		30B	3000K	85	2520	N/A	101				
		35B	3500K	85	2575	N/A	103				
		40B	4000K	85	2600	N/A	104				

DS-WS05-_____ - _____

¹Reference output shows 25W output. Multiply by 0.7 to determine output for 17W combinations.

Example: DS-WS05-F930A-WT

wacighting.com

Phone (800) 526.2588

Fax (800) 526.2585

Headquarters, East Manufacturing Facility

44 Harbor Park Drive

Port Washington, NY 11050

South East Manufacturing Facility

1600 Distribution Ct

Lithia Springs, GA 30122

Central Manufacturing Facility

1700 South J Elmer Freeway, Ste 100

Cedar Hill, TX 75104

West Manufacturing Facility

1750 S Archibald Ave

Ontario, CA 91761