

# WAC LIGHTING

## ICBINR 5CCT

### Ceiling and Wall Mount

Fixture Type: \_\_\_\_\_  
Catalog Number: \_\_\_\_\_  
Project: \_\_\_\_\_  
Location: \_\_\_\_\_

Model & Size	Color Temp & CRI	Watt	Lumens	Finish
FM-616G2 6"	9CS 2700K/3000K/3500K/4000K/5000K - 90	16W	1050	WT White

Example: **FM-616G2-9CS-WT**

#### DESCRIPTION

Multiple mid-powered LEDs illuminate the acrylic diffuser uniformly without socket shadows, which are common in conventional flush mounts.

#### FEATURES

- Multiple LED array for uniform illumination
- Imitates a traditional 6" line voltage recessed downlight with an R30 light bulb
- 5-CCT Switchable between 2700K and 5000K
- Driver installed within the Junction Box, driver dimension: 2.875" dia x 0.875" deep
- 5 year warranty

#### SPECIFICATIONS

<b>Construction</b>	Aluminum with translucent diffuser
<b>Power:</b>	16W
<b>Input:</b>	120 VAC, 50/60Hz
<b>Dimming:</b>	ELV: 100-5% , TRIAC: 100-5%
<b>Light Source:</b>	Integrated LED
<b>Lens:</b>	Translucent acrylic diffuser
<b>Rated Life:</b>	50,000 Hours
<b>Mounting:</b>	Retrofit over a 5" or 6" recessed can or install over a 4" junction box or a combination 3/0-4/0 electrical box, Can be mounted on ceiling or wall in all orientations
<b>Finish:</b>	Electrostatically Powder Coated: White
<b>Operating Temp:</b>	-4°F to 104°F (-20°C to 40°C)
<b>Standards:</b>	ETL, cETL, Damp Location Listed, ADA, Title 24 JA8 Compliant



#### FINISHES:



White