

# WAC LIGHTING

## 60W/96W, 120-277VAC/24VDC

### Remote Power Supply - Gemini & Basics

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

#### Model & Product

PS-24DC-U60R-BT Remote Enclosed Power Supply 100-277VAC Input 24VDC Output 60 Watt  
PS-24DC-U96R-BT Remote Enclosed Power Supply 100-277VAC Input 24VDC Output 96 Watt

#### L x W x H

7.4IN x 3.62IN x 1IN  
8.66IN x 3.66IN x 1.6IN

Example: **PS-24DC-U60R-BT**

#### DESCRIPTION

This class 2 and class P, UL & cUL listed enclosed electronic power supply is the perfect solution for wiring multiple low voltage fixtures. Class 2 power supplies are intrinsically safer power supplies because they are compartmentalized to allow no greater than 5 amps of current to be drawn on each compartment. Enclosure cover is easy to remove. Power supply has knockouts on three sides with clips for line voltage wiring. Secondary wiring for class 2 power supplies do not require conduit sheathed cable or clamp wiring techniques. This power supply has a low minimum load requirement of 6W to allow the use of LED products. May be dimmed using a TRIAC or electronic low voltage dimmer.

#### FEATURES

- Short circuit, over current, over voltage, over temperature protection.
- Class 2 Output
- 6W minimum load; 60 maximum load for PS-24DC-U60R-BT
- 9.6W minimum load; 96 maximum load for PS-24DC-U96R-BT
- 5 year warranty

#### SPECIFICATIONS

**Input:** 100-277 VAC, 50/60Hz  
**Dimming:** ELV: 100-5% , TRIAC: 100-5%  
**Rated Life:** 50000 Hours  
**Finish:** BLACK  
**Operating Temp:** -4°F to 104°F (-20°C to 60°C)  
**Standards:** UL, cUL, Damp Location Listed



#### FINISHES:



BLACK

# WAC LIGHTING

**60W/96W, 120-277VAC/24VDC**  
Remote Power Supply - Gemini & Basics

Fixture Type: \_\_\_\_\_

Catalog Number: \_\_\_\_\_

Project: \_\_\_\_\_

Location: \_\_\_\_\_

---

## ACCESSORIES

---

*Model*

*Description*

*Finish*

---