# INSTALLATION AND SAFETY INSTRUCTIONS

## **FOR YOUR SAFETY**

WARNING: BE SURE THE ELECTRICITY TO THE WIRES YOU ARE WORKING ON IS SHUT OFF; EITHER THE FUSE IS REMOVED OR THE CIRCUIT BREAKER IS SHUT OFF.

**GENERAL** You don't need special tools to install this fixture. Be sure to follow the steps in the order given. Under no circumstances should a fixture be hung on house electrical wires, nor should a swag type fixture be installed on a ceiling which contains a radiant type heating system. Read instructions carefully. If you are unclear as to how to proceed, consult a qualified electrician. NOTE: Proper wiring is essential for the safe operation of this fixture.

## GENERAL

You don't need special tools to install this fixture. Be sure to follow the steps in the order given. Under no circumstances should a fixture be hung on house electrical wires, nor should a swag type fixture be installed on a ceiling, which contains a radiant type heating system. Read instructions carefully. If you are unclear as to how to proceed, consult a qualified electrician. **NOTE:** Proper wiring is essential for the safe operation of this fixture.

# FIXTURE ASSEMBLY

Carefully removed the fixture from the carton and check that all parts are included as shown in figure. Be careful not to misplace any of the screws or parts, which are needed to install this fixture.

## **INSTALLATION**

**IMPORTANT:** Do not attach fixture directly to outlet box. **STEP1:**Install universal mounting plate (B) on the outlet box, make sure the two ribs (E) on the mounting plate (B) must be in the vertical position.

Proceed to connect wires:

# **GROUNDING INSTRUCTIONS**

**STEP 1**: Insert the green grounding screw into the hole with two raised dimples on the circular strap. Wrap the ground wire from the fixture (if supplied) around the green grounding screw, then connect it to ground wire from the outlet box (if not fixed on the outlet box) using a wire connector (not supplied). If ground wire from the fixture is not supplied, wrap the ground wire (if not fixed on the outlet box) from the outlet box around the green grounding screw and tighten it. **NEVER CONNECT GROUND WIRE TO** 


#### **BLACK OR WHITE POWER SUPPLY WIRES.**

STEP 2: Take note of the color of the wire(s) on your fixture.

GROUP A: Connect to Black	GROUP B: Connect to White
House Wire	House Wire
BLACK	WHITE
*PARALLEL WIRE (round &	*PARALLEL WIRE (square &
smooth)	ridged)
WHITE OR GREY	WHITE OR GREY WITHOUT
WITH TRACER	TRACER
BROWN GOLD OR BLACK	BROWN, GOLD OR
WITHOUT TRACER	BLACK WITH TRACER

**NOTE:** When parallel wire (SPT-I & SPT-2) is used, the tracer wire is square shaped or ridged and the less tracer wire is round in shape or smooth (seen best when viewed from wire end.)

- **STEP 2:** Take your fixture wire(s) from group A and place evenly against the black wire from the outlet box. Do NOT twist wires together before using wire connectors.
- STEP 3: Fit a wire connector (not supplied) over the wires and screw the connector clockwise until you feel a firmness.
- **STEP 4:** Try gently to pull the connector off the wires. If you can pull the connector off, carefully re-do steps 3 and 4, as above, and check again for a firm connection.
- **STEP 5:** Connect the fixture wire from group B to the white wire from the outlet box in the same manner.



# FINIAL ASSEMBLY

**STEP1:** After wires are connected, tuck them carefully insideoutlet box.

**STEP2:** Put the back plate (D) over the universal mounting plate (B) and secure it to universal mounting plate rib (E) with mounting screw (C).

STEP3:Slide glass shade (G) through socket (F).


**STEP4:**Place socket ring (H) onto socket (F) and tighten glass shade (G) carefully. Install bulb (I)(not included) to socket (F). (Do not exceed the maximum capacity recommended on the socket.)

#### **CLEANING**

To clean, wipe fixture with a soft cloth. Clean glass with amild soap. Do notuseabrasivematerialssuchasscouringpadsor powders, steel wool or abrasive paper.

#### **ORDERING PARTS**

Keep this sheet for future reference, and in case youneedto order replacementparts. Allparts for this fixture can be ordered from place of purchase. Besure to use exact wording from illustration when ordering parts.



notexactlymatchthefixtureenclosed. However,theinstallations doapplytothis fixture. ITEM NO:815-1S 815-2S